

Cold shrink Kit for 1-5/8 in or 1-1/4 in to 1/4 in through 1/2 in connections



Product Classification

Product Type	Cold shrink kit
Ordering Note	CommScope® standard product (Global)

General Specifications

Application	Provides additional moisture seal for cable connections
Applications per Kit	One 1/4 in–1/2 in to 1-5/8 in or 1-1/4 in
Cable Family	AL7-50 AVA7-50 EFX2-50 ETS1-50T ETS2-50T FSJ1-50B FSJ1-75 FSJ2-50 FSJ4-50B FSJ4-75A LDF1-50 LDF2-50 LDF4-50A LDF4-75 LDF6-50 LDF7-50A VXL6-50 VXL7-50

Color	Black
--------------	-------

Dimensions

Width	72.39 mm 2.85 in
Length	330.2 mm 13 in
Cable Diameter for Seal, maximum	30.48 mm 1.2 in
Cable Diameter for Seal, minimum	7.37 mm 0.29 in
Inner Diameter	69.85 mm 2.75 in
Nominal Size	1-1/4 in 1-5/8 in 1/2 in 1/4 in 3/8 in

Material Specifications

Material Type	EPDM rubber
----------------------	-------------

Environmental Specifications

UV Resistance Test Method	UV condensation reference ASTM-G-53, light source UVA 340 fluorescent
----------------------------------	---

lamp

UV Resistance, minimum with no degradation

≥1000 hours

Weather Resistance Test Method

04AS00-03.6.0 | MIL-STD-1344A, Method 1002

Packaging and Weights

Height, packed

299.72 mm | 11.8 in

Width, packed

81.28 mm | 3.2 in

Length, packed

81.28 mm | 3.2 in

Included

One EPDM rubber tube | One sealing foam strip

Packaging quantity

1

Weight, gross

0.34 kg | 0.75 lb

Regulatory Compliance/Certifications

Agency

Classification

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

REACH-SVHC

Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS

Compliant

UK-ROHS

Compliant

