

UDS-PANELS



Ultra-density splice (UDS) fiber optic panels

- UDS fiber panels feature a modular, ultra-dense design that scales effortlessly while holding maintenance costs and space requirements to a minimum
- Each UDS fiber panel is delivered with a complete installation kit that includes a ship along kit with all necessary accessories to install the given panel
- UDS fiber panels are perfect suited for areas like meet-me rooms and interconnects

ULTRA-DENSE, EASY-TO-MANAGE FIBER CONNECTIVITY

Compact design maximizes fiber port density within each rack, while a removable rear splicing drawer and superior cable routing ensure easy fiber access and control.

- Up to 288 fibers in a 2RU size or 864 fibers in a 6RU
- Connect up to 6,912 fibers in a single rack
- Intelligent cable routing supports multiple incoming cable configurations

SEAMLESS FLEXIBLE SCALING

The modular design supports your migration to increasingly higher fiber-count ribbon cables, giving you more headroom for future growth.

- Combine up to eight 6RU panels to accept 6,912 fibers in a single rack
- The ability to pay as you grow allows for incremental spending as needed
- Available with Method A or Method B Enhanced polarity

FASTER, SIMPLIFIED DEPLOYMENT

With a completely removable splice drawer, open access to trays, and ample pigtail slack, the ultra-density splice panel can be installed by one person in about half the time of comparable solutions.

- 12-fiber ribbon pigtails allow fast mass fusion splicing
- Internal, translucent shutters provide dust protection while making troubleshooting easy
- Shutters automatically actuated by connector insertion enable one-handed operation

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Fiber patch/splice panel
Product Series	UDS

General Specifications

Color	Black White
Intelligence Type	Not iPatch® ready

UDS-PANELS

Interface, front	LC/APC LC/UPC
Pigtail Assembly Type	12-fiber, ribbon
Rack Type	EIA 19 in
Shelf Movement	Sliding, rear

Environmental Specifications

Safety Standard	cUL US 1863
------------------------	-------------

Packaging and Weights

Packaging quantity	1
---------------------------	---