



#### **Product Classification**

Product Type Premium elliptical waveguide

Product Brand HELIAX®
Product Series Premium

General Specifications

Jacket Color Black

Performance Note Values typical, unless otherwise stated

**Dimensions** 

Diameter Over Jacket (E Plane)33.5 mm1.319 inDiameter Over Jacket (H Plane)20.3 mm0.799 in

**Cable Volume** 334 L/km | 3.595 ft³/kft

Electrical Specifications

eTE11 Mode Cutoff 6.5 GHz

**Group Delay at Frequency** 125 ns/100 ft @ 11.200 GHz | 410 ns/100 m @ 11.200 GHz

**Operating Frequency Band** 10.0 – 10.7 GHz

VSWR/Return Loss

Frequency Band VSWR Return Loss (dB)

**10.0–10.7 GHz** 1.08 28.3

Attenuation

Frequency (GHz) Attenuation (dB/100 m) Attenuation (dB/100 ft) Average Power (kW) Group Velocity %

**10.0** 10.814 3.296 1.486 76

Page 1 of 2

# EWP90-100

10.2	10.649	3.246	1.509	77.1
10.4	10.503	3.201	1.53	78.1
10.6	10.371	3.161	1.549	79

### Material Specifications

Conductor Material Corrugated copper

Jacket Material PE

### Mechanical Specifications

Minimum Bend Radius, Multiple Bends (E Plane)180 mm | 7.087 inMinimum Bend Radius, Multiple Bends (H Plane)480 mm | 18.898 inMinimum Bend Radius, Single Bend (E Plane)150 mm | 5.906 inMinimum Bend Radius, Single Bend (H Plane)330 mm | 12.992 inMaximum Twist6.562 °/m | 2 °/ft

#### **Environmental Specifications**

Installation temperature

-40 °C to +60 °C (-40 °F to +140 °F)

Operating Temperature

-55 °C to +85 °C (-67 °F to +185 °F)

Storage Temperature

-70 °C to +85 °C (-94 °F to +185 °F)

Attenuation, Ambient Temperature $75 \,^{\circ}\text{F}$  |  $23.889 \,^{\circ}\text{C}$ Average Power, Ambient Temperature $104 \,^{\circ}\text{F}$  |  $40 \,^{\circ}\text{C}$ Average Power, Temperature Rise $42 \,^{\circ}\text{C}$  |  $107.6 \,^{\circ}\text{F}$ 

Packaging and Weights

**Cable weight** 0.48 kg/m | 0.323 lb/ft

## Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

