

RVVPX306.11B-T2



6-port sector antenna, 2x 694–960 and 4x 1695–2690 MHz, 65° HPBW, 3x RET with manual override and SBT on every RF port

- Each port has an integrated bias tee, and each band has its own smart switch that automatically selects between bias tee or AISG inputs according to a predetermined priority table
- All Internal RET actuators are in SRET configuration, with dedicated AISG ports for each band

General Specifications

Antenna Type	Sector
Band	Multiband
Grounding Type	RF connector body grounded to reflector and mounting bracket
Performance Note	Outdoor usage Wind loading figures are validated by wind tunnel measurements described in white paper WP-112534-EN
Radome Material	Fiberglass, UV resistant
Radiator Material	Low loss circuit board
Reflector Material	Aluminum
RF Connector Interface	7-16 DIN Female
RF Connector Location	Bottom
RF Connector Quantity, high band	4
RF Connector Quantity, low band	2
RF Connector Quantity, total	6

Remote Electrical Tilt (RET) Information


RET Interface	8-pin DIN Female 8-pin DIN Male
RET Interface, quantity	1 female 3 male
Input Voltage	10–30 Vdc
Internal Bias Tee	Port 1 Port 2 Port 3 Port 4 Port 5 Port 6
Internal RET	High band (2) Low band (1)
Power Consumption, idle state, maximum	2 W
Power Consumption, normal conditions, maximum	13 W
Protocol	3GPP/AISG 2.0 (Single RET)

Dimensions

RVVPX306.11B-T2

Width	350 mm 13.78 in
Depth	208 mm 8.189 in
Length	1584 mm 62.362 in
Net Weight, without mounting kit	24.7 kg 54.454 lb

Array Layout



Array	Freq (MHz)	Conns	RET (SRET)	AISG RET UID
R1	694-960	1-2	1	ARxxxxxxxxxxxxxxxxx1
Y1	1695-2690	3-4	2	ARxxxxxxxxxxxxxxxxx2
Y2	1695-2690	5-6	3	ARxxxxxxxxxxxxxxxxx3

Left Right
Bottom

(Sizes of colored boxes are not true depictions of array sizes)

Port Configuration

RVVPX306.11B-T2



RVVPX306.11B-T2



Electrical Specifications

Impedance	50 ohm
Operating Frequency Band	1695 – 2690 MHz 694 – 960 MHz
Polarization	±45°
Total Input Power, maximum	650 W @ 50 °C

Electrical Specifications

Frequency Band, MHz	694–790	790–890	890–960	1695–1920	1920–2180	2300–2690
Gain, dBi	14.3	14.9	15.2	17.2	17.8	18.4
Beamwidth, Horizontal, degrees	69	67	66	62	62	64
Beamwidth, Vertical, degrees	16.5	14.6	13.6	7.5	6.7	5.5
Beam Tilt, degrees	2–12	2–12	2–12	0–10	0–10	0–10
USLS (First Lobe), dB	15	18	21	18	20	19
Front-to-Back Ratio at 180°, dB	30	32	33	36	37	38
Isolation, Cross Polarization, dB	27	27	27	28	28	28
Isolation, Inter-band, dB	28	28	28	28	28	28
VSWR Return loss, dB	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0

RVVPX306.11B-T2

PIM, 3rd Order, 2 x 20 W, dBc	-150	-150	-150	-150	-150	-150
Input Power per Port at 50°C, maximum, watts	150	150	150	150	150	100

Electrical Specifications, BASTA

Frequency Band, MHz	694–790	790–890	890–960	1695–1920	1920–2180	2300–2690
Gain by all Beam Tilts, average, dBi	14.1	14.8	15	16.9	17.6	18.2
Gain by all Beam Tilts Tolerance, dB	±0.4	±0.3	±0.3	±0.5	±0.5	±0.3
Gain by Beam Tilt, average, dBi	2° 14.2 7° 14.1 12° 14.0	2° 14.8 7° 14.8 12° 14.7	2° 15.0 7° 15.1 12° 15.0	0° 16.8 5° 16.9 10° 16.9	0° 17.6 5° 17.6 10° 17.6	0° 18.2 5° 18.3 10° 18.2
Beamwidth, Horizontal Tolerance, degrees	±1.2	±1	±1.6	±2.9	±1.9	±3.2
Beamwidth, Vertical Tolerance, degrees	±1	±0.8	±0.5	±0.5	±0.5	±0.4
USLS, beampeak to 20° above beampeak, dB	18	18	22	18	19	19
Front-to-Back Total Power at 180° ± 30°, dB	25	25	26	29	27	29
CPR at Boresight, dB	20	19	20	19	20	19
CPR at Sector, dB	12	12	15	10	11	9

Mechanical Specifications

Wind Loading @ Velocity, frontal	255.0 N @ 150 km/h (57.3 lbf @ 150 km/h)
Wind Loading @ Velocity, lateral	214.0 N @ 150 km/h (48.1 lbf @ 150 km/h)
Wind Loading @ Velocity, maximum	540.0 N @ 150 km/h (121.4 lbf @ 150 km/h)
Wind Loading @ Velocity, rear	270.0 N @ 150 km/h (60.7 lbf @ 150 km/h)
Wind Speed, maximum	241 km/h (150 mph)

Packaging and Weights

Width, packed	420 mm 16.535 in
Depth, packed	310 mm 12.205 in
Length, packed	1760 mm 69.291 in
Weight, gross	41.4 kg 91.271 lb

Regulatory Compliance/Certifications

Agency	Classification
---------------	-----------------------

RVVPX306.11B-T2

CHINA-ROHS	Above maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant/Exempted
UK-ROHS	Compliant/Exempted




Included Products

T-041-GL-E	-	Adjustable Tilt Pipe Mounting Kit for 2.0"-4.5" (60-115mm) OD round members for panel antennas. Includes 2 clamp sets.
------------	---	------------------------------------------------------------------------------------------------------------------------

* Footnotes

Performance Note	Severe environmental conditions may degrade optimum performance
-------------------------	-----------------------------------------------------------------

T-041-GL-E



Adjustable Tilt Pipe Mounting Kit for 2.0"-4.5" (60-115mm) OD round members for panel antennas. Includes 2 clamp sets.

Product Classification

Product Type Adjustable tilt mounting kit

General Specifications

Application Outdoor

Color Silver

Dimensions

Compatible Length, maximum 1500 mm | 59.055 in

Compatible Length, minimum 1200 mm | 47.244 in

Compatible Diameter, maximum 115 mm | 4.528 in

Compatible Diameter, minimum 60 mm | 2.362 in

Antenna-to-Pipe Distance 85 mm | 3.346 in

Bracket-to-Bracket Distance 976 mm | 38.425 in

Weight, net 5.5 kg | 12.125 lb

Material Specifications

Material Type Galvanized steel

Mechanical Specifications

Mechanical Tilt 0°-12° in steps of 2°

Packaging and Weights

Included Brackets | Hardware

Packaging quantity 1

Regulatory Compliance/Certifications

Agency	Classification
CE	Compliant with the relevant CE product directives

T-041-GL-E

CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

