

# T-10-UW-43-M-I6

---



Low PIM Termination 10 W Load, 340-6000 MHz

## Product Classification

<b>Regional Availability</b>	Asia   Australia/New Zealand   EMEA   Latin America   North America
<b>Product Type</b>	Termination Load

## General Specifications

<b>Device Type</b>	Termination Load
<b>Application</b>	Indoor
<b>Color</b>	Silver
<b>Inner Contact Plating</b>	Silver
<b>Interface</b>	4.3-10 Male
<b>Outer Contact Plating</b>	Trimetal

## Dimensions

<b>Length</b>	145 mm   5.709 in
<b>Diameter, maximum</b>	44 mm   1.732 in

## Electrical Specifications

<b>3rd Order IMD</b>	-165 dBc
<b>3rd Order IMD Test Method</b>	Two +40 dBm carriers
<b>Average Power, maximum</b>	10 W
<b>Impedance</b>	50 ohm
<b>Operating Frequency Band</b>	340 – 6000 MHz
<b>VSWR at Frequency Band</b>	1.2:1 @ 555–2700 MHz   1.3:1 @ 2700–6000 MHz   1.4 @ 340–555 MHz

## Environmental Specifications

<b>Operating Temperature</b>	-25 °C to +50 °C (-13 °F to +122 °F)
<b>Relative Humidity</b>	Up to 100%

# T-10-UW-43-M-I6

---

## Packaging and Weights

<b>Height, packed</b>	65 mm   2.559 in
<b>Width, packed</b>	85 mm   3.346 in
<b>Length, packed</b>	200 mm   7.874 in
<b>Weight, gross</b>	0.6 kg   1.323 lb
<b>Weight, net</b>	0.52 kg   1.146 lb

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
CHINA-ROHS	Above maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant/Exempted
UK-ROHS	Compliant/Exempted

