DB224-E

1-port omni exposed dipole antenna, 138–150 MHz, 360° HPBW, fixed electrical tilt

- Broad response
- Two-piece mast for ease of shipping

General Specifications

Antenna Type Omni

Band Single band

Color Silver

Grounding Type RF connector inner conductor and body grounded to reflector and mounting bracket

Performance Note Outdoor usage

Radiator MaterialAluminumRF Connector InterfaceN MaleRF Connector LocationBottom

RF Connector Quantity, low band 1
RF Connector Quantity, total 1

Dimensions

Length 6858 mm | 270 in

Net Weight, without mounting kit 17.2 kg | 37.919 lb

Electrical Specifications

Impedance 50 ohm

Operating Frequency Band 138 – 150 MHz

Polarization Vertical

Electrical Specifications

Frequency Band, MHz 138-150

Gain, dBi 8.1

Beamwidth, Horizontal,

360

degrees

Beamwidth, Vertical, degrees 16

COMMSC PE®

DB224-E

Beam Tilt, degrees

VSWR | Return loss, dB 1.5 | 14.0 Input Power per Port, 500

maximum, watts

Mechanical Specifications

Wind Loading @ Velocity, maximum 560.5 N @ 100 mph (126.0 lbf @ 100 mph)

Wind Speed, maximum 130 km/h (81 mph)

0

Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system



Included Products

DB365-OS – Pipe Mounting Kit that consists of two clamps for mounting antennas to round members 1.25 -

3.5 in (35 - 89 mm) OD round members.

* Footnotes

Performance Note Severe environmental conditions may degrade optimum performance



DB365-0S

Pipe Mounting Kit that consists of two clamps for mounting antennas to round members 1.25 - 3.5 in (35 - 89 mm) OD round members.

Product Classification

Product Type Pipe mount kit

General Specifications

ApplicationOutdoorColorSilver

Dimensions

Compatible Diameter, maximum88.9 mm | 3.5 inCompatible Diameter, minimum33 mm | 1.299 inWeight, net3.2 kg | 7.055 lb

Material Specifications

Material Type Galvanized steel

Packaging and Weights

Included Brackets | Hardware

Packaging quantity 2

Weight, gross 3.6 kg | 7.937 lb

Regulatory Compliance/Certifications

Agency Classification

CE Compliant with the relevant CE product directives

CHINA-ROHS Below maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant



