

PICABOND® Connector, 1000 loose piece, 400 Vdc, red

- Lightweight, compact, and economical means of splicing multiconductor telephone cable
- No prestripping or cutting required, can tap without service interruptions, eliminates "turndowns"
- Color-coded to indicate size and type of wire; used for butt, straight, bridge and half-tap splicing applications

OBSOLETE

This product was discontinued on: June 7, 2021

Product Classification

Regional Availability

Australia/New Zealand | EMEA | Latin America | North America

Product Type Splice

Product Brand PICABOND®
Product Series PICABOND

General Specifications

Connector Color Code Red

Connector Sealant Unfilled

Connector Splicing Type Bridge | Butt | Full bridge | Half-tap | Straight (In-line)

Dimensions

Compatible Conductor Gauge, solid 24–19 AWG

Electrical Specifications

Safety Voltage Rating 400 Vdc

Material Specifications

Contact Base Material Phosphor Bronze

Contact Plating Material Tin

Insulation Material Air Core PIC | Paper or Pulp

Environmental Specifications



60947-3

Operating Temperature -40 °C to +60 °C (-40 °F to +140 °F)

Environmental Space Outdoor

Packaging and Weights

Packaging quantity 1000

Packaging Type Loose piece

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant

