CS3119N001 | 102K011-37/U-(S50)



102K Heat-Shrinkable Cable End Cap kit, pressurized, for 9 to 16 mm cable diameter, 60 mm long, 1500 pcs

- Bonds directly to the cable jacket eliminating the need for additional components
- Prevention of water ingress to allow long term storage without risk of moisture penetration
- Used extensively by major telephone companies and telephone cable manufacturers

OBSOLETE

This product was discontinued on: October 28, 2018

Product Classification

Regional Availability	North America
Product Type	Heat shrink end cap
Product Series	102K
General Specifications	
Color	Black
Sealant Type	Hotmelt adhesive
Dimensions	
Length	60 mm 2.362 in
Single Cable Diameter, maximum	16 mm 0.63 in
Single Cable Diameter, minimum	9 mm 0.354 in
Expanded Wall Thickness, minimum	2.8 mm 0.11 in
Material Specifications	
Material Type	Polyolefin
Environmental Specifications	5
Environmental Space	Aerial Ducted

Packaging and Weights

Packaging quantity

1500

Page 1 of 2

©2023 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: December 6, 2023



CS3119N001 | 102K011-37/U-(S50)

Packaging Type

Bag | Carton

Regulatory Compliance/Certifications

Agency

CHINA-ROHS

REACH-SVHC

ROHS

UK-ROHS



Classification
Below maximum concentration value
Compliant as per SVHC revision on www.commscope.com/ProductCompliance
Compliant
Compliant

Page 2 of 2

©2023 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: December 6, 2023

