CS3120N001 | 102K022-37/U-(S50)



102K Heat-Shrinkable Cable End Cap kit, pressurized, for 16 to 26 mm cable diameter, 85 mm long, 600 pcs

- Bonds directly to the cable jacket eliminating the need for additional components
- Prevention of water ingress to allow long term storage without risk of moisture penetration
- Used extensively by major telephone companies and telephone cable manufacturers

OBSOLETE

This product was discontinued on: October 28, 2018

Product Classification

Regional Availability North America

Product TypeHeat shrink end cap

Product Series 102K

General Specifications

Color Black

Sealant Type Hotmelt adhesive

Dimensions

Length 85 mm | 3.346 in

Single Cable Diameter, maximum26 mm | 1.024 inSingle Cable Diameter, minimum16 mm | 0.63 in

Expanded Wall Thickness, minimum 3.2 mm | 0.126 in

Material Specifications

Material Type Polyolefin

Environmental Specifications

Environmental Space Aerial | Ducted

Packaging and Weights

Packaging quantity 600



CS3120N001 | 102K022-37/U-(S50)

Packaging Type Bag | Carton

Regulatory Compliance/Certifications

Agency Classification

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

