

RCT6-S-1A-RNA



RCT6, RADIAX® Coaxial Radiating Cable with Bump, 1700–2500 MHz, tuned foil, 1-1/4 in, black non-halogenated, fire retardant polyolefin jacket

Product Classification

Brand	RADIAX®
Product Series	RCT6
Product Type	Radiating cable

Construction Materials

Jacket Material	Non-halogenated, fire retardant polyolefin
Dielectric Material	Foam PE
Inner Conductor Material	Corrugated copper tube
Jacket Color	Black
Outer Conductor Material	Copper foil

Dimensions

Nominal Size	1-1/4 in
Diameter Over Jacket, maximum	39.116 mm 1.540 in
Inner Conductor OD	0.5200 in 14.2080 mm
Outer Conductor OD	1.340 in 34.030 mm
Cable Weight	0.43 lb/ft 0.64 kg/m

Electrical Specifications

Operating Frequency Band	1700 – 2500 MHz
Optimum Operating Frequency Band	2300 – 2500 MHz
Polarization	Vertical
VSWR Installed, typical, 1700–2500 MHz	1.30
VSWR on Reel, typical	1.43
Cable Impedance	50 ohm ±2 ohm
dc Resistance, Inner Conductor	0.530 ohms/kft 1.740 ohms/km
dc Resistance, Outer Conductor	0.900 ohms/kft 2.953 ohms/km
dc Test Voltage	8500 V
Insulation Resistance	100000 Mohms•km
Jacket Spark Test Voltage (rms)	10000 V
Peak Power	180.0 kW

RCT6-S-1A-RNA

Velocity 91%

Environmental Specifications

Installation Temperature -30 °C to +60 °C (-22 °F to +140 °F)
Operating Temperature -30 °C to +80 °C (-22 °F to +176 °F)
Storage Temperature -30 °C to +80 °C (-22 °F to +176 °F)

General Specifications

Cable Type Radiating Mode (RCT) Series

Mechanical Specifications

Bending Moment 15.5 N-m | 11.4 ft lb
Flat Plate Crush Strength 80.0 lb/in | 1.4 kg/mm
Indication of Slot Alignment Yes; bumps face the wall
Minimum Bend Radius, Single Bend 381.00 mm | 15.00 in
Recommended Distance from the Wall 101.6 mm | 4.0 in
Recommended Hanger Spacing 1.3 m | 4.3 ft
Tensile Strength 168 kg | 370 lb
Fire Retardancy Test Method IEC 60332-1 | IEC 60332-3C-24
Smoke Index Test Method IEC 61034
Toxicity Index Test Method IEC 60754-1 | IEC 60754-2

Standard Conditions

Attenuation Test Method IEC 61196-4
Attenuation Tolerance ±5%
Attenuation, Ambient Temperature 20 °C | 68 °F
Average Power, Ambient Temperature 40 °C | 104 °F
Average Power, Inner Conductor Temperature 100 °C | 212 °F
Coupling Loss Test Method IEC 61196-4
Coupling Loss Tolerance ±5 dB

Electrical Performance

Frequency	Attenuation (dB/100 m)	Attenuation (dB/100 ft)	Coupling Loss 50%	Coupling Loss 95%
1700 MHz	3.50	1.07	75	77
1800 MHz	3.60	1.10	72	76
1900 MHz	3.80	1.16	70	72
2000 MHz	3.90	1.19	69	73
2100 MHz	4.10	1.25	67	70
2200 MHz	4.30	1.31	67	70
2300 MHz	4.50	1.37	66	69
2400 MHz	4.80	1.46	63	66

RCT6-S-1A-RNA

2500 MHz 5.20

1.58

62

65

Regulatory Compliance/Certifications

Agency

ISO 9001:2015

Classification

Designed, manufactured and/or distributed under this quality management system

