

195PSCR-CR

SMC Male Right Angle for CNT-195 braided cable

Product Classification

Brand	CNT®
Product Type	Braided cable connector

General Specifications

Interface	SMC Male
Body Style	Right angle

Electrical Specifications

Operating Frequency Band	0 – 6000 MHz
Average Power at Frequency	150.0 W @ 900 MHz
Cable Impedance	50 ohm
Connector Impedance	50 ohm
RF Operating Voltage, maximum (vrms)	335.00 V
dc Test Voltage	750 V
Outer Contact Resistance, maximum	2.50 mOhm
Inner Contact Resistance, maximum	5.00 mOhm
Insulation Resistance, minimum	5000 MOhm
Peak Power, maximum	2.20 kW
Insertion Loss, typical	0.05 dB

Mechanical Specifications

Outer Contact Attachment Method	Crimp
Outer Contact Plating	Gold
Inner Contact Plating	Gold
Inner Contact Attachment Method	Solder
Interface Durability	500 cycles
Interface Durability Method	IEC 61169-9:9.5
Connector Retention Tensile Force	134 N 30 lbf
Connector Retention Torque	0.17 N-m 0.13 ft lb
Insertion Force	10.00 N 2.25 lbf
Insertion Force Method	IEC 61169-9:9.3.5
Pressurizable	No
Coupling Nut Proof Torque	0.71 N-m 0.52 ft lb
Coupling Nut Proof Torque Method	IEC 61169-9:9.3.6
Coupling Nut Retention Force	150.00 N 33.72 lbf
Coupling Nut Retention Force Method	IEC 61169-9:9.3.11

195PSCR-CR

Dimensions

Nominal Size	0.195 in
Diameter	7.90 mm 0.31 in
Length	26.80 mm 1.06 in
Weight	5.00 g 0.01 lb
Width	7.90 mm 0.31 in

Environmental Specifications

Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Storage Temperature	-65 °C to +125 °C (-85 °F to +257 °F)
Water Jetting Test Mating	Mated
Water Jetting Test Method	IEC 60529:2001, IP65
Mechanical Shock Test Method	IEC 60068-2-27
Climatic Sequence Test Method	IEC 60068-1
Damp Heat Steady State Test Method	IEC 60068-2-3
Thermal Shock Test Method	IEC 60068-2-14
Vibration Test Method	IEC 60068-2-6
Corrosion Test Method	IEC 60068-2-11

Standard Conditions

Attenuation, Ambient Temperature	20 °C 68 °F
Average Power, Ambient Temperature	40 °C 104 °F
Average Power, Inner Conductor Temperature	100 °C 212 °F

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU

ISO 9001:2015

China RoHS SJ/T 11364-2014

Classification

Compliant by Exemption

Designed, manufactured and/or distributed under this quality management system

Above Maximum Concentration Value (MCV)



* Footnotes

Insertion Loss, typical $0.05\sqrt{f}$ (GHz) (not applicable for elliptical waveguide)