

CommScope, Inc. of North Carolina **LETTER REPORT**

SCOPE OF WORK

Testing of a cabling configuration performance to the requirements of IEEE Std 802.3™ for Type 4 remote powering applications at extended distance

REPORT NUMBER

105853508CRT-001I

ISSUE DATE

24-June-2024

REVISED DATE

None

TESTS START DATE

24-June-2024

TESTS END DATE

24-June-2024

PAGES

5

DOCUMENT CONTROL NUMBER

GFT-OP-10a (6-March-2017)

© 2017 INTERTEK



LETTER REPORT

24-June -2024

Intertek Report No. 105853508CRT-001I

Intertek Project No. G105853508

Mr. Wayne Hopkinson
CommScope, Inc. of North Carolina
3642 US Hwy 70 East
Claremont NC 28610
USA

Subject: Performance testing of category 6 unshielded channel per IEEE 802.3™ for support of Type 4 remote powering applications commonly referred as PoE++

Dear Mr. Hopkinson:

This letter report represents the results of our evaluation of the above referenced product(s) to the requirements contained in the following document(s):

IEEE Std 802.3™-2022 Standard for Ethernet, Approved 13-May-2022

SECTION 1 SUMMARY

Intertek wishes to inform you that the power delivery tests have been performed on your channel configuration. This testing was performed under project G105853508 and quotation Qu-01450453 issued 06-May-2024. Compliant results were obtained for the relevant tests contained in section 145 of IEEE 802.3™ for channel transmission performance.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.


SECTION 2 NON-CONFORMANCES

None

SECTION 3 TEST CONFIGURATION

The client supplied a 2-connector unshielded channel as illustrated below.

The samples were received on 24-June-2024 and were production samples in undamaged condition.



Component Id	Manufacturer	Description	Part number
1	CommScope	Ceiling Connector Assembly (CCA)	CO1SJO2-88N018
2	CommScope	U/UTP CMP horizontal cable	GigaREACH 2073A
3	CommScope	Modular jack	MGS400
4	CommScope	Modular cord	CPC3312-03F010

SECTION 4 TEST EQUIPMENT USED

The following test equipment was used to conduct the testing.

Test equipment used	Model number	Control number	Calibration due date
AEM multifunction cable tester	TestPro CV100	J388	20-December-2024
Keysight LCR Meter	4263B	E355	19-October-2024
Temperature/humidity meter	OM-EL-USB-2-LCD	H243	23-May-2025

SECTION 5
TESTING

The tables below represent a summary of the tests and results. The DC resistance test data is enclosed to this letter report.

Test description	IEEE 802.3 section	Result
DC loop resistance	145.1.3	Compliant
DC resistance unbalance within a pair	145A.1	Compliant
DC resistance unbalance between pairs	145A.3	Compliant
Functional power delivery	Various	Compliant

The cabling configuration was confirmed to meet the minimum 71 W power delivery for Type 4 remote powering applications at ambient temperature. This was done using the external load function of the AEM TestPro CV100 multifunction cable tester as shown in the following screenshot.



The ambient conditions during the testing were 20°C and 62% relative humidity.


SECTION 6

PROJECT STATUS & ACTION

Issuance of this letter report completes the power delivery testing of this channel cabling configuration per IEEE 802.3™ covered by Intertek Project No. G105853508 and quotation Qu-01450453. The test results are compliant with the requirements of the standard and sections referred to on pages 2 and 4. The testing was performed at the client's facility located in Claremont, NC.

If there are any questions regarding the results contained in this report, or any of the other services offered by Intertek, please do not hesitate to contact your dedicated Intertek Project Manager.

Completed by:	David Ayers
Title:	Technician
Signature:	
Date	24-June-2024

Reviewed by:	Antoine Pelletier
Title:	Project Engineer
Signature	
Date:	24-June-2024

Please note: this Letter Report does not represent authorization for the use of any Intertek certification marks.



Low Frequency Report

Client	CommScope	Report No	105853508CRT-0011@20C
Specification	IEEE 802-3bt Type 4		
Part No	2073A	Length (m)	253.5
Test Started	6/24/2024	Temperature	20 °C
Description	2 Connector Channel		
Operator Name	Antoine Pelletier	Test Status	Complies

DC Resistance (Ohms)

45	12	36	78	Limit (Ohms)
11.2750	11.7940	11.3690	11.6870	
11.2990	11.7920	11.3490	11.7220	

Resistance Unbalanced (%)

45	12	36	78	Limit (%)
0.11	0.01	0.09	0.15	3.00

Resistance Unbalanced Pair-Pair (%)

45 - 12	45 - 36	45 - 78	12 - 36	12 - 78	36 - 78	Limit (%)
2.19	0.32	1.82	1.87	0.38	1.50	7.00

DC Loop Resistance (Ohms)

45	12	36	78	Limit (Ohms)
22.5740	23.5860	22.7180	23.4090	25.0000