



Fiber Indoor cable, TeraSPEED® Riser Distribution, interlocking aluminum armored with riser jacket, 12 fiber single-unit, Gel-free, Singlemode G.652.D and G.657.A1, Feet jacket marking, Yellow jacket color

## Product Classification

|                              |   |
|------------------------------|---|
| <b>Regional Availability</b> | Asia   Australia/New Zealand   Latin America   Middle East/Africa   North America |
| <b>Portfolio</b>             | CommScope®  |
| <b>Product Type</b>          | Fiber indoor cable  |
| <b>Product Series</b>        | R-DZ  |

## General Specifications

|                             |                       |
|-----------------------------|-----------------------|
| <b>Armor Type</b>           | Interlocking aluminum |
| <b>Cable Type</b>           | Distribution          |
| <b>Construction Type</b>    | Armored               |
| <b>Fiber Type, quantity</b> | 12                    |
| <b>Jacket Color</b>         | Yellow                |
| <b>Jacket Marking</b>       | Feet                  |
| <b>Subunit Type</b>         | Gel-free              |
| <b>Total Fiber Count</b>    | 12                    |

## Dimensions

|                             |                    |
|-----------------------------|--------------------|
| <b>Diameter Over Armor</b>  | 10.8 mm   0.425 in |
| <b>Diameter Over Jacket</b> | 12.8 mm   0.504 in |

## Mechanical Specifications

|  |                     |
|--|---------------------|
| <b>Minimum Bend Radius, loaded</b>       | 192 mm   7.559 in   |
| <b>Minimum Bend Radius, unloaded</b>     | 128 mm   5.039 in   |
| <b>Tensile Load, long term, maximum</b>  | 200 N   44.962 lbf  |
| <b>Tensile Load, short term, maximum</b> | 667 N   149.948 lbf |

# 760127316 | R-012-DZ-8W-FSUYL

---

|                                |                                       |
|--------------------------------|---------------------------------------|
| <b>Compression</b>             | 85 N/mm   485.363 lb/in               |
| <b>Compression Test Method</b> | FOTP-41   IEC 60794-1 E3              |
| <b>Flex</b>                    | 25 cycles                             |
| <b>Flex Test Method</b>        | FOTP-104   IEC 60794-1 E6             |
| <b>Impact</b>                  | 35 N-m   309.776 in lb                |
| <b>Impact Test Method</b>      | FOTP-25   IEC 60794-1 E4              |
| <b>Strain</b>                  | See long and short term tensile loads |
| <b>Strain Test Method</b>      | FOTP-33   IEC 60794-1 E1              |
| <b>Twist</b>                   | 10 cycles                             |
| <b>Twist Test Method</b>       | FOTP-85   IEC 60794-1 E7              |
| <b>Vertical Rise, maximum</b>  | 140 m   459.318 ft                    |

## Optical Specifications

|                   |                                  |
|-------------------|----------------------------------|
| <b>Fiber Type</b> | G.652.D and G.657.A1, TeraSPEED® |
|-------------------|----------------------------------|

## Environmental Specifications

|                                      |                                       |
|--------------------------------------|---------------------------------------|
| <b>Installation temperature</b>      | -20 °C to +70 °C (-4 °F to +158 °F)   |
| <b>Operating Temperature</b>         | -20 °C to +70 °C (-4 °F to +158 °F)   |
| <b>Storage Temperature</b>           | -40 °C to +70 °C (-40 °F to +158 °F)  |
| <b>Cable Qualification Standards</b> | ANSI/ICEA S-83-596   Telcordia GR-409 |
| <b>Environmental Space</b>           | Riser                                 |
| <b>Flame Test Listing</b>            | NEC OFCR (ETL) and c(ETL)             |
| <b>Flame Test Method</b>             | UL 1666                               |

## Environmental Test Specifications

|                                      |                                     |
|--------------------------------------|-------------------------------------|
| <b>Heat Age</b>                      | -20 °C to +85 °C (-4 °F to +185 °F) |
| <b>Heat Age Test Method</b>          | IEC 60794-1 F9                      |
| <b>Low High Bend</b>                 | -20 °C to +70 °C (-4 °F to +158 °F) |
| <b>Low High Bend Test Method</b>     | FOTP-37   IEC 60794-1 E11           |
| <b>Temperature Cycle</b>             | -20 °C to +70 °C (-4 °F to +158 °F) |
| <b>Temperature Cycle Test Method</b> | FOTP-3   IEC 60794-1 F1             |

## Packaging and Weights

# 760127316 | R-012-DZ-8W-FSUYL

---

**Cable weight**

146 kg/km | 98.107 lb/kft

## Regulatory Compliance/Certifications

**Agency****Classification**

CHINA-ROHS

Below maximum concentration value

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

REACH-SVHC

Compliant as per SVHC revision on [www.commscope.com/ProductCompliance](http://www.commscope.com/ProductCompliance)

ROHS

Compliant



## Included Products

CS-8W-TB - TeraSPEED® Singlemode Fiber

## \* Footnotes

**Operating Temperature** Specification applicable to non-terminated bulk fiber cable