594946-001-00 | FFT8-10TQ



FFT Complete RF Tap, 8-way, 1.2 GHz Full-Feature Equalizable, 10 dB nominal tap value, 12 A Power passing

- *Product complies with the Build America, Buy America Act (BABAA) requirements of the Infrastructure Investment and Jobs Act of 2021 (Pub. L. 117- 58, §§ 70901-70953), or is the subject of a waiver approved by the Secretary of Commerce or designee. Compliance requirements and waiver applicability vary based on government funding program. Check the laws and regulations for your specific program.
- Support DOCSIS® 3.1 expanded bandwidth up to 1218 MHz
- Improve network performance with signal conditioning plug-ins
- High quality RF connection with auto-seize F- connectors
- Maintain existing installed base with compatibility back to "F" series FFT housings
- Standard faceplate only options for cost effective upgrades to existing FFT deployments
- High level of network resilience with 6 kV surge resistance on feederline and F-ports
- Blank tap option FFT*-PBA-V for future expansion
- Maintain RF and AC connections with faceplate removed with integrated bypass capability

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Product Type	RF tap
Product Series	FFT
Government Requirements	Build America Buy America (BABA) compliant*
General Specifications	
Location of Manufacturing	Waived per BABA waiver for BEAD Program
Number of Ports	8
Dimensions	
Height	101.6 mm 4 in
Depth	73.66 mm 2.9 in
Length	142.24 mm 5.6 in
Electrical Specifications	
Bandwidth	5 – 1218 MHz MHz
Insertion Loss, tap, nominal	10 dB
Power Passing at 60/90V, maximum	12 A

Page 1 of 2

©2025 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: April 29, 2025



594946-001-00 | FFT8-10TQ

 Surge Protection, F port
 6 kV Combination Wave

 Surge Protection, input/out ports
 6 kV Combination Wave

 Environmental Specifications
 -40 °C to +60 °C (-40 °F to +140 °F)

 Operating Temperature
 -40 °C to +60 °C (-40 °F to +140 °F)

 Packaging and Weights
 0.454 kg | 1 lb

 Regulatory Combination
 0.454 kg | 1 lb

 Agency
 Classification

 CHINA-ROHS
 Above maximum commentation value

ROHS

UK-ROHS

Classification Above maximum concentration value Compliant Compliant



Page 2 of 2

©2025 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: April 29, 2025

