



Indoor/Outdoor Fiber Optic Cable, 12-fiber, loose tube, LSZH, OM3, 2000 m

OBSOLETE

This product was discontinued on: December 30, 2022

Replaced By:

760249714 Fiber indoor/outdoor cable, Gel-filled Central Tube, 12 fiber, Multimode OM3, Meters jacket
C-012-CN-5Y-M12BK/28G/093 marking, Black jacket color

Product Classification

Regional Availability	Asia
Portfolio	CommScope®
Product Type	Fiber indoor/outdoor cable
Product Series	C-LN

General Specifications

Cable Type	Loose tube
Subunit Type	Gel-filled
Jacket Color	Black
Jacket Marking	Meters
Fibers per Subunit, quantity	12
Total Fiber Count	12

Dimensions

Cable Length	2000 m 6,561.68 ft
Diameter Over Jacket	8 mm 0.315 in

Mechanical Specifications

Minimum Bend Radius, loaded	160 mm 6.299 in
Minimum Bend Radius, unloaded	80 mm 3.15 in
Tensile Load, long term, maximum	800 N 179.847 lbf

Tensile Load, short term, maximum 1800 N | 404.656 lbf

Optical Specifications

Fiber Type OM3

Optical Specifications, Wavelength Specific

10 Gbps Ethernet Distance 300 m @ 850 nm
Attenuation, maximum 1.50 dB/km @ 1,300 nm | 3.50 dB/km @ 850 nm
Bandwidth, Laser, minimum 2,000 MHz-km @ 850 nm
Bandwidth, OFL, minimum 1,500 MHz-km @ 850 nm | 500 MHz-km @ 1,300 nm
Standards Compliance TIA-492AAAC (OM3)

Environmental Specifications

Installation temperature -10 °C to +60 °C (+14 °F to +140 °F)
Operating Temperature -20 °C to +70 °C (-4 °F to +158 °F)
Storage Temperature -40 °C to +70 °C (-40 °F to +158 °F)
Environmental Space Low Smoke Zero Halogen (LSZH)

Packaging and Weights

Cable weight 73 kg/km | 49.054 lb/kft

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant



* Footnotes

Operating Temperature Specification applicable to non-terminated bulk fiber cable