

NGF-VSPM-7000L



Next Generation Frame (NGF) Fiber MicroVAM Block, unloaded, putty white, left oriented

Product Classification

Regional Availability	EMEA Latin America North America
Product Type	Fiber VAM block
Product Series	NGF

General Specifications

Functionality	Multiplexing Splitting
Application	Used in NGF-style frames only
Body Style	Left orientation
Color	Putty white
Color, front	Putty white
Door Type, front	Compression latch Hinged
Growth Configuration	Unloaded
Module/Adapter Pack Slots, quantity	12
Rack Type	NGF
Shelf Movement	Fixed

Dimensions

Height	299.72 mm 11.8 in
Width	454.914 mm 17.91 in
Depth	132.08 mm 5.2 in

Material Specifications

Finish	Powder coated
Material Type	Steel

NGF-VSPM-7000L

Environmental Specifications

Operating Temperature	-5 °C to +50 °C (+23 °F to +122 °F)
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Relative Humidity	Up to 80%, non-condensing
Qualification Standards	Telcordia GR-449-CORE

Packaging and Weights

Packaging quantity	1
---------------------------	---

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

