


760109470 | 360G2 Cassette 12-LC-LS-AQ-Pigtails



360G2 Cassette 12 LC Multimode Aqua with Pigtails iPatch Ready

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Fiber cassette with pigtails

General Specifications

Adapter Color	Aqua
Intelligence Type	iPatch® ready
Interface Feature, front	Standard
Interface, front	LC
Total Fibers, quantity	12
Total Ports, quantity, front	12

Dimensions

Height	30.48 mm 1.2 in
Width	91.44 mm 3.6 in
Pigtail Length	1.5 m 4.921 ft
Depth	119.38 mm 4.7 in

Optical Specifications

Fiber Type	OM4, LazrSPEED® 550
Insertion Loss, typical	0.27 dB
Return Loss, minimum	20 dB

Environmental Specifications

760109470 | 360G2 Cassette 12-LC-LS-AQ-Pigtails

Safety Standard UL

Packaging and Weights

Packaging quantity 1

Regulatory Compliance/Certifications

Agency

ISO 9001:2015

REACH-SVHC

Classification

Designed, manufactured and/or distributed under this quality management system

Compliant as per SVHC revision on www.commscope.com/ProductCompliance



Included Products

700207004
MFA-LC12-AQ-SHUTTERED — LazrSPEED® LC Multiport Shuttered Adapter, Aqua, Single Pack

- 860251875 — LazrSPEED® 550 LC 0.9 mm Pigtail, blue, 1.5 m
- 860251883 — LazrSPEED® 550 LC 0.9 mm Pigtail, orange, 1.5 m
- 860251891 — LazrSPEED® 550 LC 0.9 mm Pigtail, green, 1.5 m
- 860251909 — LazrSPEED® 550 LC 0.9 mm Pigtail, brown, 1.5 m
- 860251917 — LazrSPEED® 550 LC 0.9 mm Pigtail, slate, 1.5 m
- 860251925 — LazrSPEED® 550 LC 0.9 mm Pigtail, white, 1.5 m
- 860251933 — LazrSPEED® 550 LC 0.9 mm Pigtail, red, 1.5 m
- 860251941 — LazrSPEED® 550 LC 0.9 mm Pigtail, black, 1.5 m
- 860251958 — LazrSPEED® 550 LC 0.9 mm Pigtail, yellow, 1.5 m
- 860251966 — LazrSPEED® 550 LC 0.9 mm Pigtail, violet, 1.5 m
- 860251974 — LazrSPEED® 550 LC 0.9 mm Pigtail, rose, 1.5 m

700207004 | MFA-LC12-AQ-SHUTTERED

LazrSPEED® LC Multiport Shuttered Adapter, Aqua, Single Pack

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Fiber adapter
Product Brand	LazrSPEED®
Product Series	MFA

General Specifications

Body Style	Ganged
Color	Aqua
Interface	LC
Interface Feature	Standard
Mounting	No flange
Shuttered	Yes
Total Ports, quantity	12

Material Specifications

Alignment Sleeve Material	Zirconia (ceramic)
----------------------------------	--------------------

Optical Specifications

Fiber Mode	Multimode
-------------------	-----------

Packaging and Weights

Packaging quantity	1
---------------------------	---

Regulatory Compliance/Certifications

700207004 | MFA-LC12-AQ-SHUTTERED

Agency

ISO 9001:2015


REACH-SVHC

**Classification**

Designed, manufactured and/or distributed under this quality management system

Compliant as per SVHC revision on www.commscope.com/ProductCompliance

LazrSPEED® 550 LC 0.9 mm Pigtail, blue, 1.5 m



Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Fiber pigtail, simplex
Product Brand	LazrSPEED®

General Specifications

Construction Type	Pigtail, jacketed
Interface, Connector A	LC/UPC
Jacket Color	Blue
Total Fibers, quantity	1

Mechanical Specifications

Cable Retention Strength, maximum	1.00 lb @ 0 ° 1.00 lb @ 90 °
--	--------------------------------

Optical Specifications

Fiber Type	OM4, LazrSPEED® 550
-------------------	---------------------

Environmental Specifications

Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Environmental Space	Plenum


Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

860251875



LazrSPEED® 550 LC 0.9 mm Pigtail, orange, 1.5 m



Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Fiber pigtail, simplex
Product Brand	LazrSPEED®

General Specifications

Construction Type	Pigtail, jacketed
Interface, Connector A	LC/UPC
Jacket Color	Orange
Total Fibers, quantity	1

Mechanical Specifications

Cable Retention Strength, maximum	1.00 lb @ 0 ° 1.00 lb @ 90 °
--	--------------------------------

Optical Specifications

Fiber Type	OM4, LazrSPEED® 550
-------------------	---------------------

Environmental Specifications

Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Environmental Space	Plenum


Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

860251883



LazrSPEED® 550 LC 0.9 mm Pigtail, green, 1.5 m



Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Fiber pigtail, simplex
Product Brand	LazrSPEED®

General Specifications

Construction Type	Pigtail, jacketed
Interface, Connector A	LC/UPC
Jacket Color	Green
Total Fibers, quantity	1

Mechanical Specifications

Cable Retention Strength, maximum	1.00 lb @ 0 ° 1.00 lb @ 90 °
--	--------------------------------

Optical Specifications

Fiber Type	OM4, LazrSPEED® 550
-------------------	---------------------

Environmental Specifications


Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Environmental Space	Plenum

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system



LazrSPEED® 550 LC 0.9 mm Pigtail, brown, 1.5 m



Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Fiber pigtail, simplex
Product Brand	LazrSPEED®

General Specifications

Construction Type	Pigtail, jacketed
Interface, Connector A	LC/UPC
Jacket Color	Brown
Total Fibers, quantity	1

Mechanical Specifications

Cable Retention Strength, maximum	1.00 lb @ 0 ° 1.00 lb @ 90 °
--	--------------------------------

Optical Specifications

Fiber Type	OM4, LazrSPEED® 550
-------------------	---------------------

Environmental Specifications


Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Environmental Space	Plenum

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system



LazrSPEED® 550 LC 0.9 mm Pigtail, slate, 1.5 m



Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Fiber pigtail, simplex
Product Brand	LazrSPEED®

General Specifications

Construction Type	Pigtail, jacketed
Interface, Connector A	LC/UPC
Jacket Color	Slate
Total Fibers, quantity	1

Mechanical Specifications

Cable Retention Strength, maximum	1.00 lb @ 0 ° 1.00 lb @ 90 °
--	--------------------------------

Optical Specifications

Fiber Type	OM4, LazrSPEED® 550
-------------------	---------------------

Environmental Specifications


Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Environmental Space	Plenum

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system



LazrSPEED® 550 LC 0.9 mm Pigtail, white, 1.5 m



Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Fiber pigtail, simplex
Product Brand	LazrSPEED®

General Specifications

Construction Type	Pigtail, jacketed
Interface, Connector A	LC/UPC
Jacket Color	White
Total Fibers, quantity	1

Mechanical Specifications

Cable Retention Strength, maximum	1.00 lb @ 0 ° 1.00 lb @ 90 °
--	--------------------------------

Optical Specifications

Fiber Type	OM4, LazrSPEED® 550
-------------------	---------------------

Environmental Specifications

Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Environmental Space	Plenum


Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

860251925



LazrSPEED® 550 LC 0.9 mm Pigtail, red, 1.5 m



Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Fiber pigtail, simplex
Product Brand	LazrSPEED®

General Specifications

Construction Type	Pigtail, jacketed
Interface, Connector A	LC/UPC
Jacket Color	Red
Total Fibers, quantity	1

Mechanical Specifications

Cable Retention Strength, maximum	1.00 lb @ 0 ° 1.00 lb @ 90 °
--	--------------------------------

Optical Specifications

Fiber Type	OM4, LazrSPEED® 550
-------------------	---------------------

Environmental Specifications

Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Environmental Space	Plenum


Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

860251933



LazrSPEED® 550 LC 0.9 mm Pigtail, black, 1.5 m



Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Fiber pigtail, simplex
Product Brand	LazrSPEED®

General Specifications

Construction Type	Pigtail, jacketed
Interface, Connector A	LC/UPC
Jacket Color	Black
Total Fibers, quantity	1

Mechanical Specifications

Cable Retention Strength, maximum	1.00 lb @ 0 ° 1.00 lb @ 90 °
--	--------------------------------

Optical Specifications

Fiber Type	OM4, LazrSPEED® 550
-------------------	---------------------

Environmental Specifications

Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Environmental Space	Plenum


Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

860251941



LazrSPEED® 550 LC 0.9 mm Pigtail, yellow, 1.5 m



Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Fiber pigtail, simplex
Product Brand	LazrSPEED®

General Specifications

Construction Type	Pigtail, jacketed
Interface, Connector A	LC/UPC
Jacket Color	Yellow
Total Fibers, quantity	1

Mechanical Specifications

Cable Retention Strength, maximum	1.00 lb @ 0 ° 1.00 lb @ 90 °
--	--------------------------------

Optical Specifications

Fiber Type	OM4, LazrSPEED® 550
-------------------	---------------------

Environmental Specifications

Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Environmental Space	Plenum


Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

860251958



LazrSPEED® 550 LC 0.9 mm Pigtail, violet, 1.5 m



Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Fiber pigtail, simplex
Product Brand	LazrSPEED®

General Specifications

Construction Type	Pigtail, jacketed
Interface, Connector A	LC/UPC
Jacket Color	Violet
Total Fibers, quantity	1

Mechanical Specifications

Cable Retention Strength, maximum	1.00 lb @ 0 ° 1.00 lb @ 90 °
--	--------------------------------

Optical Specifications

Fiber Type	OM4, LazrSPEED® 550
-------------------	---------------------

Environmental Specifications

Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Environmental Space	Plenum


Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

860251966



LazrSPEED® 550 LC 0.9 mm Pigtail, rose, 1.5 m



Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Fiber pigtail, simplex
Product Brand	LazrSPEED®

General Specifications

Construction Type	Pigtail, jacketed
Interface, Connector A	LC/UPC
Jacket Color	Rose
Total Fibers, quantity	1

Mechanical Specifications

Cable Retention Strength, maximum	1.00 lb @ 0 ° 1.00 lb @ 90 °
--	--------------------------------

Optical Specifications

Fiber Type	OM4, LazrSPEED® 550
-------------------	---------------------

Environmental Specifications

Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Environmental Space	Plenum

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

860251974

