# FJWMPMPDF

**Base Product** 



Singlemode MPO (Unpinned) to MPO (Unpinned), InstaPATCH® 360 Pre-terminated Indoor/Outdoor Trunk Cable, 24-Fiber, Low Smoke Zero Halogen

#### Product Classification

**Construction Type** 

Regional Availability	Asia   Australia/New Zealand   China   Europe   India   Latin America   Middle East/Africa   North America
Portfolio	CommScope®
Product Type	Fiber trunk cable assembly
Product Brand	SYSTIMAX InstaPATCH® 360
Ordering Note	For lengths greater than 999 ft (304 m), orders must be in meters   Minimum length may vary based on cable configuration
General Specifications	
Color, boot A	Black
Color, connector A	Green
Color, boot B	Black
Color, connector B	Green

InstaPATCH® 360 trunk/extension/cross-connect, indoor/outdoor

Furcation Color	Yellow
Interface, Connector A	MPO-12/APC Female
Interface, Connector B	MPO-12/APC Female
Jacket Color	Black
Polarity	Method B (LL)
Fibers per Subunit, quantity	12
Total Fibers, quantity	24
Dimensions	

3 - 999

Cable Assembly Length Range (m)

Page 1 of 3

©2025 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: February 19, 2025



# FJWMPMPDF

Cable Assembly Length Range (ft)

10 - 999

### Ordering Tree

	E	BASE C		ĿIJ	·
Jac	ket Color		Breakout Length / Option	L	ength
H	Black	A	33 inch breakout, no gland		
		В	33 inch breakout, with gland		
		С	33 inch breakout, with pulling grip		
		1	33/60 inch breakout, no gland		
		2	33/60 inch breakout, with gland on side A	L	юм
		3	33/60 inch breakout, with pulling grip and gland on side A	F	Feet Meter
		4	33/120 inch breakout, no gland		
		5	33/120 inch breakout, with gland on side A		
		6	33/120 inch breakout, with pulling grip and gland on side A		
		т	33 inch breakout, with gland on side A		
		U	33 inch breakout, with pulling grip and gland on side A		
		v	60 inch breakout, no gland		
		w	60 inch breakout, with pulling grip		
		Р	120 inch breakout, no gland		
		Q	120 inch breakout, with pulling grip		

#### Mechanical Specifications

Cable Retention Strength, maximum	11.24 lb @ 0 °   4.40 lb @ 90 °
Optical Specifications	
Fiber Mode	Singlemode
Fiber Type	G.652.D   G.657.A1, TeraSPEED®

#### **Environmental Specifications**

#### **Operating Temperature**

-40 °C to +70 °C (-40 °F to +158 °F)

Page 2 of 3

©2025 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: February 19, 2025



# FJWMPMPDF

Environmental Space	Dual Rated LSZH/Riser   Indoor/Outdoor   Outdoor		
Regulatory Compliance/Certifications			
Agency	Classification		
CHINA-ROHS	Below maximum concentration value		
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system		
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance		
ROHS	Compliant		
UK-ROHS	Compliant		
Included Droducte			

#### Included Products

760151803 Z-024-MP-8W-F12BK/D	_	Fiber Indoor/Outdoor cable, TeraSPEED® Low Smoke Zero Halogen Riser MPO Trunk, 24 fiber with 12 fiber subunits, Gel-free, Singlemode G.652.D and G.657.A1, Feet jacket marking, Black jacket color, Dca flame rating
860366137	-	MP012, LOW LOSS, FEMALE, Singlemode, GREEN, 3mm

Page 3 of 3

©2025 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: February 19, 2025

