

Category 6_A Shielded AMP-TWIST Modular Jack

1711342-2, 1711160-2, 1711343-2, 1711295-2

CommScope's Category 6_A F/UTP AMP-TWIST modular jacks deliver the next generation of 10G performance while maintaining high density solutions for data center and LAN environments. The shielded AMP-TWIST modular jacks meet or exceed all the requirements for Category 6A ANSI/TIA and ISO standards.

The shielded AMP-TWIST 6_A modular jacks offer superior noise immunity to eliminate alien crosstalk and RFI/EMI while offering integrated mechanical bonding and grounding through normal installation practices. These modular jacks have a slim profile and are compatible with SL Series style faceplates. The jacks offer integral hinged dust cover or without dust cover in both back (180°) or side (90°) cable entry options. Universal wiring labels permit termination to either T568A or T568B wiring patterns. The AMP-TWIST modular jacks contain integrated cutting blades allowing all four pairs of a four pair cable to be terminated at one time. This termination technology provides for a quick and reliable termination.

Specification (text in brackets [] requires a choice)

Modular jacks shall be unkeyed, 4-pair, RJ-45, with an integrated shield and shall fit in a .790" X .582" opening. Modular jacks shall terminate using the AMP NETCONNECT SL Series modular jack termination tool part number 1725150-3 (or 1725150-1 after removing the tool's lacing fixture), and be color-coded for both T568A and T568B wiring. Each modular jack shall be wired to [T568A or T568B] and shall accommodate cable with a maximum O.D. of 9.00 mm. Cables shall enter the jack at [180°, 90° from the right or 90° from the left]. The insulation displacement contacts shall be capable of terminating 24-22 AWG solid or 26-24 AWG stranded conductors with a maximum insulation diameter of 1.60 mm. The insulation displacement contacts shall be paired, with additional space between pairs to improve crosstalk performance. Modular jacks shall utilize a secondary PC board, separate from the signal path, for crosstalk compensation. Each modular jack shall meet the ANSI/TIA-568-C.2 and ISO 11801, Category 6A performance standards and the requirements listed in the following table.

[Include Performance Characteristics table from page 2]

[Each jack shall incorporate an integral, hinged dust cover.] Modular jacks shall be part number [1711160-2, 1711342-2, 1711343-2 or 1711295-2].

Category 6_A Shielded AMP-TWIST Modular Jack

1711342-2, 1711160-2, 1711343-2, 1711295-2

Channel Performance Characteristics (meet or exceed ANSI/EIA/TIA, ISO/IEC and IEEE requirements)

Frequency (MHz)	Insertion Loss (dB)	NEXT (dB)	PSNEXT (dB)	ACRF (dB)	PSACRF (dB)	Return Loss (dB)	Prop Delay (ns/100m)	Prop Delay Skew (ns)	TCL (dB)	EITCL/TCTL (dB)	PSANEXT (dB)	PSAACRF / PSAEXT (dB)
0.772	2.1	65.0	62.0	65.5	62.5	19.0	585.0	50.0	40.0	32.2	67.0	67.0
1	2.3	65.0	62.0	63.3	60.3	19.0	580.0	50.0	40.0	30.0	67.0	67.0
4	4.2	63.0	60.5	51.2	48.2	19.0	562.0	50.0	40.0	18.0	67.0	65.0
8	5.8	58.2	55.6	45.2	42.2	19.0	556.7	50.0	39.5	11.9	67.0	58.9
10	6.5	56.6	54.0	43.3	40.3	19.0	555.4	50.0	38.0	10.0	67.0	57.0
16	8.2	53.2	50.6	39.2	36.2	18.0	553.0	50.0	34.9	5.9	67.0	52.9
20	9.2	51.6	49.0	37.2	34.2	17.5	552.0	50.0	33.5	4.0	67.0	51.0
25	10.2	50.0	47.3	35.3	32.3	17.0	551.2	50.0	32.0	2.0	66.0	49.0
31.25	11.5	48.4	45.7	33.4	30.4	16.5	550.4	50.0	30.4	N/A	65.1	47.1
62.5	16.4	43.4	40.6	27.3	24.3	14.0	548.6	50.0	24.4	N/A	62.0	41.1
100	20.9	39.9	37.1	23.3	20.3	12.0	547.6	50.0	20.3	N/A	60.0	37.0
200	30.1	34.8	31.9	17.2	14.2	9.0	546.5	50.0	14.3	N/A	55.5	31.0
250	33.9	33.1	30.2	15.3	12.3	8.0	546.3	50.0	12.3	N/A	54.0	29.0
300	37.4	31.7	28.8	13.7	10.7	7.2	546.1	50.0	10.8	N/A	52.8	27.5
400	43.6	28.7	25.8	11.2	8.2	6	545.8	50	8.3	N/A	51.0	24.9
500	49.3	26.1	23.2	9.28	6.3	6	545.6	50	6.3	N/A	49.5	23.0

Specifications

Materials

Modular Jack and Lacing Fixture Housing: Zinc Alloy

IDC Connecting Block: Polycarbonate, 94V-0 rated

Contacts: Beryllium copper, plated with 1.27 µm [50 µin] thick gold in localized area and 3.81 µm [150 µin] minimum thick nickel underplate and 3.8 µin minimum thick tin in solder area over 1.27 µm minimum thick nickel underplate

Cutting Blade and Shield Point Contact: Stainless Steel

Insulation Displacement Contacts: Phosphorous bronze, plated with 3.81 µm [150 µin] minimum thick matte tin over 1.27 µm [50 µin] minimum thick nickel underplate

Electrical Characteristics

Voltage: 150VAC max.

Operating Temperature: -40° to 70°C (-40° to 158°F)

Mechanical Characteristics

Modular Jack: 750 mating cycles

Insulation Displacement Contacts: Accept solid, 24-22 AWG conductors or stranded 26-24 AWG conductors with a maximum insulation diameter of 1.60 mm

Cutout Opening: See diagrams on next page

Cable Outside Diameter: Accepts cables with a maximum O.D. of 9.00 mm

Packaging


Modular Jack: 24 pieces per carton

UL listed to U.S. and Canadian safety standards, reference UL file number: E81956

Category 6_A Shielded AMP-TWIST Modular Jack

1711342-2, 1711160-2, 1711343-2, 1711295-2

Cutout Dimensions



Ordering Information

Product Description	Form Factor	Cable Exit	Integrated Dust Cover	Part Number
Cat 6 _A AMP-TWIST Shielded Modular Jacks	SL Series	180° (back)	–	1711342-2
			Dust Cover	1711160-2
		90° (side)	–	1711343-2
			Dust Cover	1711295-2



www.commscope.com

Visit our website or contact your local CommScope representative for more information.

© 2015 CommScope, Inc. All rights reserved.

All trademarks identified by ® or ™ are registered trademarks or trademarks, respectively, of CommScope, Inc. This document is for planning purposes only and is not intended to modify or supplement any specifications or warranties relating to CommScope products or services.

PS-318061.1-AE (11/15)