

APS-XT



Antenna Orientation and Location Sensing System

- Available as a retrofit to site-installed ANDREW and Third Party antennas
- Monitors Azimuth, Tilt, Roll, Latitude, Longitude and Elevation
- Works with AISG 2.1 controllers as an Alignment Sensor Device and Geographic Location Sensor
- Works with AISG 2.0 controllers in RET emulation mode
- Verify Installations
- Long Term Monitoring

Product Classification

Product Type RET actuator

General Specifications

AISG Input Connector	8-pin DIN Male
AISG Input Connector Quantity	1
AISG Output Connector	8-pin DIN Female
AISG Output Connector Quantity	1
Azimuth Note	Accuracy may be affected by installation environment and satellite visibility
Azimuth, nominal	$\pm 2.5^\circ$
Color	Gray
Elevation	± 5 m
Latitude	± 5 m
Longitude	± 5 m
Roll	$\pm 1^\circ$
Tilt	$\pm 1^\circ$

Dimensions

Height	99 mm 3.898 in
Width	325 mm 12.795 in
Depth	166 mm 6.535 in

Electrical Specifications

Input Voltage	10–30 Vdc
Boot Time	15 s

APS-XT

Boot Time Note	Exceeds AISG 2.0 and 2.1 requirements
Electromagnetic Compatibility (EMC)	CFR 47 Part 15, Subpart B, Class A EN 55022 EN 55032 EN 61000-4-2 EN 61000-4-3 EN 61000-4-4 EN 61000-4-6
Interface Protocol Signal	RS-485
Lightning Surge Capability Test Method	IEC 61000-4-5
Lightning Surge Capability Waveform	1.2/50 voltage and 8/20 current combination waveform
Lightning Surge Test Mode	Common mode
Power Consumption, maximum	3 W
Power Supply	AISG (compliant with AISG 2.1 ASD and GLS, exceeds AISG 2.0 RET)
Protocol	3GPP/AISG 2.0 compliant

Material Specifications

Material Type	ASA
----------------------	-----

Environmental Specifications

Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Relative Humidity	Up to 95%, non-condensing
Climatic Sequence Test Method	IEC 60068-2-14
Cold Exposure Test Method	IEC 60068-2-1
Corrosion Test Method	IEC 60068-2-11, Test Condition Ka IEC 60068-2-52, Test Condition Kb
Damp Heat Exposure Test Method	IEC 60068-2-30, Test Condition Db
Heat Exposure Test Method	IEC 60068-2-2
Ingress Protection Test Method	IEC 60529:2001, IP56
Packaged Product Shock Test Method	ASTM D4169 GR-63-CORE, Section 4.1.1
Rain Simulation Test Method	IEC 60068-2-18, Test Condition Ra, Method 1
UV Resistance Test Method	IEC 60068-2-5, Test Condition B
Vibration Test Method	ASTM D4169 IEC 60068-2-6

Packaging and Weights

Weight, net	1.5 kg 3.307 lb
--------------------	-------------------

Regulatory Compliance/Certifications

Agency	Classification
CE	Compliant with the relevant CE product directives

APS-XT

CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant
UK-ROHS	Compliant

