

HBXXX-6516DS-VTM | HBXXX-6516DS-A3M



6-port sector antenna, 6x 1710–2180 MHz, 65° HPBW, RET compatible

- Excellent solution for site sharing and maximizing capacity
- Excellent front-to-back ratio, USLS, VSWR, and PIM specifications to enhance network quality
- Ideal solution for dense urban, suburban site applications
- Each antenna downtilt can be independently adjusted for greater flexibility in network optimization

OBSOLETE

This product was discontinued on: March 30, 2024

Replaced By:

6P-6M-A3
V3-65A-R3

6-port sector antenna, 6x 1695–2690 MHz, 65° HPBW, 3x RET

General Specifications

Antenna Type	Sector
Band	Single band
Color	Light Gray (RAL 7035)
Grounding Type	RF connector inner conductor and body grounded to reflector and mounting bracket
Performance Note	Outdoor usage
Radome Material	Fiberglass, UV resistant
Radiator Material	Low loss circuit board
RF Connector Interface	7-16 DIN Female
RF Connector Location	Bottom
RF Connector Quantity, high band	6
RF Connector Quantity, mid band	0
RF Connector Quantity, low band	0
RF Connector Quantity, total	6

Remote Electrical Tilt (RET) Information

Model with Factory Installed AISG 2.0 Actuator	HBXXX-6516DS-A3M
--	------------------

Dimensions

HBXXX-6516DS-VTM | HBXXX-6516DS-A3M

Width	500 mm 19.685 in
Depth	90 mm 3.543 in
Length	1309 mm 51.535 in
Net Weight, without mounting kit	15.3 kg 33.731 lb

Electrical Specifications

Impedance	50 ohm
Operating Frequency Band	1710 – 2180 MHz
Polarization	±45°

Electrical Specifications

Frequency Band, MHz	1710–1880	1850–1990	1920–2180
Gain, dBi	17.9	17.7	17.8
Beamwidth, Horizontal, degrees	64.1	63.4	62.3
Beamwidth, Vertical, degrees	7.8	7.4	7
Beam Tilt, degrees	2–10	2–10	2–10
USLS (First Lobe), dB	17	17	17
Front-to-Back Ratio at 180°, dB	32	35	35
CPR at Boresight, dB	23	26	24
CPR at Sector, dB	6.8	6.8	6
Isolation, Cross Polarization, dB	30	30	30
VSWR Return loss, dB	1.4 15.6	1.4 15.6	1.4 15.6
PIM, 3rd Order, 2 x 20 W, dBc	-150	-150	-150
Input Power per Port, maximum, watts	300	300	300

Mechanical Specifications

Wind Loading @ Velocity, frontal	802.0 N @ 150 km/h (180.3 lbf @ 150 km/h)
Wind Loading @ Velocity, lateral	111.0 N @ 150 km/h (25.0 lbf @ 150 km/h)
Wind Loading @ Velocity, rear	860.0 N @ 150 km/h (193.3 lbf @ 150 km/h)
Wind Speed, maximum	241 km/h (150 mph)

Packaging and Weights

Width, packed	663 mm 26.102 in
Depth, packed	278 mm 10.945 in

HBXXX-6516DS-VTM | HBXXX-6516DS-A3M

Length, packed	1782 mm 70.158 in
Weight, gross	18.6 kg 41.006 lb

Regulatory Compliance/Certifications

Agency	Classification
CE	Compliant with the relevant CE product directives
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant



Included Products

600899A-2	–	Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.
-----------	---	---

* Footnotes

Performance Note	Severe environmental conditions may degrade optimum performance
------------------	---

600899A-2



Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members.
Kit contains one scissor top bracket set and one bottom bracket set.

Product Classification

Product Type Downtilt mounting kit

General Specifications

Application Outdoor

Color Silver

Dimensions

Compatible Diameter, maximum 114.3 mm | 4.5 in

Compatible Diameter, minimum 61 mm | 2.402 in

Weight, net 3.9 kg | 8.598 lb

Material Specifications

Material Type Galvanized steel

Packaging and Weights

Included Brackets | Hardware

Packaging quantity 1

Weight, gross 4.2 kg | 9.259 lb

Regulatory Compliance/Certifications

Agency	Classification
CE	Compliant with the relevant CE product directives
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

600899A-2

