# HBXXX-6516DS-VTM | HBXXX-6516DS-A3M



### 6-port sector antenna, 6x 1710–2180 MHz, 65° HPBW, RET compatible

- Excellent solution for site sharing and maximizing capacity
- Excellent front-to-back ratio, USLS, VSWR, and PIM specifications to enhance network quality
- Ideal solution for dense urban, suburban site applications
- Each antenna downtilt can be independently adjusted for greater flexibility in network optimization

#### OBSOLETE

#### This product was discontinued on: March 30, 2024

#### Replaced By:

6P-6M-A3 V3-65A-R3

6-port sector antenna, 6x 1695–2690 MHz, 65° HPBW, 3x RET

## General Specifications

Antenna Type	Sector
Band	Single band
Color	Light Gray (RAL 7035)
Grounding Type	RF connector inner conductor and body grounded to reflector and mounting bracket
Performance Note	Outdoor usage
Radome Material	Fiberglass, UV resistant
Radiator Material	Low loss circuit board
RF Connector Interface	7-16 DIN Female
RF Connector Location	Bottom
RF Connector Quantity, high band	6
RF Connector Quantity, mid band	0
RF Connector Quantity, low band	0
RF Connector Quantity, total	6

## Remote Electrical Tilt (RET) Information

Model with Factory Installed AISG 2.0 Actuator

HBXXX-6516DS-A3M

#### Dimensions

Page 1 of 3



#### HBXXX-6516DS-VTM HBXXX-6516DS-A3M

Width	500 mm   19.685 in
Depth	90 mm   3.543 in
Length	1309 mm   51.535 in
Net Weight, without mounting kit	15.3 kg   33.731 lb
Electrical Specifications	

Impedance	50 ohm
Operating Frequency Band	1710 – 2180 MHz
Polarization	±45°

## **Electrical Specifications**

Frequency Band, MHz	1710-1880	1850-1990	1920-2180
Gain, dBi	17.9	17.7	17.8
Beamwidth, Horizontal, degrees	64.1	63.4	62.3
Beamwidth, Vertical, degrees	7.8	7.4	7
Beam Tilt, degrees	2-10	2-10	2-10
USLS (First Lobe), dB	17	17	17
Front-to-Back Ratio at 180°, dB	32	35	35
CPR at Boresight, dB	23	26	24
CPR at Sector, dB	6.8	6.8	6
Isolation, Cross Polarization, dB	30	30	30
VSWR   Return loss, dB	1.4   15.6	1.4   15.6	1.4   15.6
PIM, 3rd Order, 2 x 20 W, dBc	-150	-150	-150
Input Power per Port, maximum, watts	300	300	300

## Mechanical Specifications

Wind Loading @ Velocity, frontal	802.0 N @ 150 km/h (180.3 lbf @ 150 km/h)
Wind Loading @ Velocity, lateral	111.0 N @ 150 km/h (25.0 lbf @ 150 km/h)
Wind Loading @ Velocity, rear	860.0 N @ 150 km/h (193.3 lbf @ 150 km/h)
Wind Speed, maximum	241 km/h (150 mph)

## Packaging and Weights

Width, packed	663 mm	26.102 in
Depth, packed	278 mm	10.945 in

Page 2 of 3



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 12, 2025

# HBXXX-6516DS-VTM | HBXXX-6516DS-A3M

Length, packed

1782 mm | 70.158 in

Weight, gross

18.6 kg | 41.006 lb

## Regulatory Compliance/Certifications

Agency	Classification
CE	Compliant with the relevant CE product directives
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

### Included Products

600899A-2

Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.

## \* Footnotes

**Performance Note** Severe environmental conditions may degrade optimum performance



Page 3 of 3