

LDXX-6516DS-VTM-C3

4-port sector antenna, 4x 790–960 MHz, 65° HPBW, RET compatible



- Engineered to provide wideband capability to support “Digital Dividend” band applications, future ready
- Same physical size as existing 800/900 MHz antennas for easy site zoning
- Proven core design technology, with over 1,000,000 similar antennas deployed
- Uses the 4.3-10 connector which is 40 percent smaller than the 7-16 DIN connector

OBSOLETE

This product was discontinued on: **March 31, 2021**

General Specifications

Antenna Type	Sector
Band	Single band
Color	Light Gray (RAL 7035)
Grounding Type	RF connector inner conductor and body grounded to reflector and mounting bracket
Performance Note	Outdoor usage
Radome Material	Fiberglass, UV resistant
Radiator Material	Aluminum
RF Connector Interface	4.3-10 Female
RF Connector Location	Bottom
RF Connector Quantity, low band	4
RF Connector Quantity, total	4

Dimensions

Width	549 mm 21.614 in
Depth	165 mm 6.496 in
Length	2567 mm 101.063 in
Net Weight, without mounting kit	35.5 kg 78.264 lb

Electrical Specifications

Impedance	50 ohm
------------------	--------

LDXX-6516DS-VTM-C3

Operating Frequency Band	790 – 960 MHz
Polarization	±45°

Electrical Specifications

Frequency Band, MHz	790–862	824–894	870–960
Gain, dBi	17.5	17.9	17.5
Beamwidth, Horizontal, degrees	70	67	63.5
Beamwidth, Vertical, degrees	7.9	7.5	7.1
Beam Tilt, degrees	0–8	0–8	0–8
USLS (First Lobe), dB	17	17	17
Front-to-Back Ratio at 180°, dB	30	30	30
CPR at Boresight, dB	24	24	25
CPR at Sector, dB	16	16	12
Isolation, Cross Polarization, dB	30	30	30
Isolation, Cross Polarization, port to port, dB	30	30	30
VSWR Return loss, dB	1.4 15.6	1.4 15.6	1.4 15.6
PIM, 3rd Order, 2 x 20 W, dBc	-150	-150	-150
Input Power per Port, maximum, watts	350	350	350

Mechanical Specifications

Wind Loading @ Velocity, frontal	1,436.0 N @ 150 km/h (322.8 lbf @ 150 km/h)
Wind Loading @ Velocity, lateral	298.0 N @ 150 km/h (67.0 lbf @ 150 km/h)
Wind Loading @ Velocity, rear	2,210.0 N @ 150 km/h (496.8 lbf @ 150 km/h)
Wind Speed, maximum	241 km/h (150 mph)

Packaging and Weights

Width, packed	659 mm 25.945 in
Depth, packed	275 mm 10.827 in
Length, packed	2883 mm 113.504 in
Weight, gross	53.5 kg 117.947 lb

Regulatory Compliance/Certifications

Agency	Classification
CE	Compliant with the relevant CE product directives

LDXX-6516DS-VTM-C3

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

REACH-SVHC

Compliant as per SVHC revision on www.commscope.com/ProductCompliance



Included Products

- BSAMNT-3 – Wide Profile Antenna Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.

* Footnotes

Performance Note Severe environmental conditions may degrade optimum performance

BSAMNT-3



Wide Profile Antenna Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.

Product Classification

Product Type Downtilt mounting kit

General Specifications

Application Outdoor

Color Silver

Dimensions

Compatible Diameter, maximum 115 mm | 4.528 in

Compatible Diameter, minimum 60 mm | 2.362 in

Weight, net 6.2 kg | 13.669 lb

Material Specifications

Material Type Galvanized steel

Packaging and Weights

Included Brackets | Hardware

Packaging quantity 1

Weight, gross 6.4 kg | 14.11 lb

Regulatory Compliance/Certifications

Agency	Classification
CE	Compliant with the relevant CE product directives
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

BSAMNT-3

