

PS-1600-73



PowerShift® Module, 2 separate 2000 watts circuits per module,
Patent Pending

- Reduced capital/operating expenditures
- Engineering flexibility
- Future-ready design

Product Classification

Product Type	Module
Product Brand	PowerShift®
Product Series	V2

Dimensions

Height	1.63 in 41.402 mm
Width	4 in 101.6 mm
Depth	13.85 in 351.79 mm

Electrical Specifications

Input Current Range	0-57 AMPS@ -38VDC
Input Voltage Range	-38 to -58 Vdc
Input Voltage, nominal	-54 Vdc
Output Current Range	0-30 A
Output Voltage Range	-48 to -73 Vdc
Output Voltage Ripple	400 mVpp
Output Voltage, nominal	-56 Vdc
Electrical Safety Standard	CE IEC 60950 UL cUL
Electromagnetic Compatibility/Interference (EMC/EMI)	EN 55022 Class A
Power Efficiency	93 %
Power Efficiency, nominal	97 %
Programmable RRU Voltage, nominal	-56 Vdc
Total Output Power	2000 W, input voltage dependent

PS-1600-73

Environmental Specifications

Relative Humidity	95%, non-condensing
Ambient Temperature	-40 °C -40 °F 65 °C 149 °F
Mean Time Between Failures (MTBF) at Temperature	300,000 h @ 25 °C

Packaging and Weights

Packaging quantity	1
---------------------------	---

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant

