

CSV2GD-1.2



HomeConnect® Two-way Splitter, 5–1218 MHz, Dual Mount

OBSOLETE

Product Classification

Product Type	Coaxial splitter
Product Brand	HomeConnect®

General Specifications

Device Type	Splitter
Application	Indoor Outdoor
Mounting	Horizontal Vertical
Video Ports, quantity	2

Electrical Specifications

Insertion Loss at Frequency Band, typical	3.6 dB @ 5–400 MHz 4.5 dB @ 400–1218 MHz
Return Loss at Frequency Band, input, minimum	18 dB @ 1002–1218 MHz 20 dB @ 5–1002 MHz
Return Loss at Frequency Band, output, minimum	18 dB @ 1002–1218 MHz 20 dB @ 5–1002 MHz
Frequency Response	±0.5 dB @ 5–1218 MHz
Impedance	75 ohm
Operating Frequency Band	5 – 1218 MHz
Power Passing	No
Shielding Effectiveness, minimum	120 dB
Spurious Signals/2nd Order Harmonics, before surge	<-100 dBc
Surge Capability Test Method	ANSI/SCTE 81 Category A3 (6 kV, 200 A, Ring wave)
Surge Capability Waveform	100 kHz ring wave waveform

CSV2GD-1.2

Electrical Specifications, Isolation

Isolation at Frequency Band, output to output, minimum

20 dB @ 1002-1218 MHz | 22 dB @ 5-54 MHz | 22 dB @ 870-1002 MHz | 25 dB @ 204-870 MHz | 45 dB @ 54-204 MHz

Environmental Specifications

Operating Temperature

-40 °C to +60 °C (-40 °F to +140 °F)

Grounding and Bonding Standard

UL 467 Ground Clamp Communication

Safety Standard

SCTE

Packaging and Weights

Height, packed

215 mm | 8.465 in

Width, packed

370 mm | 14.567 in

Length, packed

495 mm | 19.488 in

Carton Quantity

320

Weight, gross

24.95 kg | 55.005 lb

Regulatory Compliance/Certifications

Agency

Classification

CE	Compliant with the relevant CE product directives
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

