	4		3	2				1		
ĺ			OR PUBLICATION				REVISIONS			
╞	© 2016 COMMSCOPE, INC. CONFIDENTIAL	AND MAY BE USED ON	AWINGS AND SPECIFICATIONS ARE THE PROPRIETARY PROPERTY OF COMMSCOPE, INC. ONLY FOR THE SPECIFIC PURPOSE AUTHORIZED IN WRITING BY COMMSCOPE, INC.		P L	LTR	DESCRIPTION	DATE	DWN	APVD
					Aź	2	DWG HAS BEEN UPDATED	03-Aug-09	JG	JS
					В	}	REV PER BNS_CD_BRAND	02FEB2017	GG	DC
_										
			—Plug ,Cable ,ID Marks ,	—Boot/Strain Relief						
					Ð					
Ĵ		r f f f								
		لسلسل								
			DIM "A"							
			DIM "A"							
_										

SCHEMATIC VIEW

2. FOR AVAILABLE DASH LENGTHS, DIM A SEE THE COMMSCOPE CATALOG

THIS DRAWING IS A C	ONTROLLED DOCUMENT.	DWN 03-Aug-09 J.GATNAU снк 03-Aug-09 M.MAQUEDA		
	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±- 1 PLC ±- 2 PLC ±- 3 PLC ±- 4 PLC ±- ANGLES ±-	APVD 03-Aug-09 J.SANBARA PRODUCT SPEC 108-93017 APPLICATION SPEC -	NAME SIZE	CAG
MATERIAL _	FINISH -	USTOMER DRAWING	АЗ	

D

С

В

А

1. RJ45 Cat 6 PATCH CABLE ASSEMBLIES ARE USED AS PATCH LEADS IN GENERIC CUSTOMER PREMISES CABLING ACCORDING TO ISO/IEC 11801. THEY CAN ALSO BE USED AS WORKSTATION/EQUIPMENT LEADS TO MAINTAIN CHANNEL PERFORMANCE.

## COMMSCOPE, INC.

PATCH CORD RJ45 Cat 6 UTP LSZH STRANDED YELLOW GE CODE DRAWING NO RESTRICTED TO **C**-1711097 \_ SCALE 1:1 <sup>rev</sup> B SHEET 1 <sup>OF</sup> 1

В

А

С

D