



Fiber OSP cable, 12-fiber, OS2, HDPE, loose tube, 12 fiber, gel-filled, Singlemode G.652.D and G.657.A1, 1000 m, Meters jacket marking, Black jacket color

Product Classification

| | |
|------------------------------|------------------------------|
| Regional Availability | Australia/New Zealand EMEA |
| Portfolio | CommScope® |
| Product Type | Fiber OSP cable |
| Product Series | O-CA |

General Specifications

| | |
|-------------------------------------|--|
| Armor Type | Corrugated steel |
| Cable Type | Loose tube |
| Subunit Type | Gel-filled |
| Filler, quantity | 1 |
| Jacket Color | Black |
| Jacket Marking | Meters |
| Jacket Marking Method | Inkjet |
| Jacket Marking Text | COMMScope GB SYSTEM F.O. CABLE 810009835/DB CSA GEL LOOSE TUBE 12X9 /125 OS2 HDPE (Serial NUMBER) (METRE MARK) |
| Fibers per Subunit, quantity | 12 |
| Total Fiber Count | 12 |

Dimensions

| | |
|-----------------------------|----------------------|
| Cable Length | 1000 m 3,280.84 ft |
| Diameter Over Jacket | 10 mm 0.394 in |

Material Specifications

| | |
|------------------------|----------------------------------|
| Jacket Material | High density polyethylene (HDPE) |
|------------------------|----------------------------------|

810009835/DB | O-012-CA-8W-M12BK/GY/HD

Mechanical Specifications

| | |
|---|----------------------|
| Minimum Bend Radius, loaded | 150 mm 5.906 in |
| Minimum Bend Radius, unloaded | 100 mm 3.937 in |
| Tensile Load, long term, maximum | 1250 N 281.011 lbf |
| Flex | 25 cycles |

Optical Specifications

| | |
|-------------------|----------------------|
| Fiber Type | G.652.D and G.657.A1 |
|-------------------|----------------------|

Optical Specifications, Wavelength Specific

| | |
|-----------------------------|---|
| Attenuation, maximum | 0.35 dB/km @ 1,300 nm 0.35 dB/km @ 1,550 nm 0.45 dB/km @ 1,310 nm |
| Standards Compliance | IEC 60794-1 TIA-492CAAB (OS2) |

Environmental Specifications

| | |
|---------------------------------|-------------------------------------|
| Installation temperature | -5 °C to +50 °C (+23 °F to +122 °F) |
| Operating Temperature | -20 °C to +70 °C (-4 °F to +158 °F) |
| Storage Temperature | -20 °C to +70 °C (-4 °F to +158 °F) |

Packaging and Weights

| | |
|---------------------|---------------------------|
| Cable weight | 104 kg/km 69.885 lb/kft |
|---------------------|---------------------------|

Regulatory Compliance/Certifications

| Agency | Classification |
|---------------|--|
| CHINA-ROHS | Below maximum concentration value |
| REACH-SVHC | Compliant as per SVHC revision on www.commscope.com/ProductCompliance |
| ROHS | Compliant |
| UK-ROHS | Compliant |



Included Products

CS-8W-250-EMEA – LightScope ZWP® Singlemode Fiber
250um

* Footnotes

810009835/DB | O-012-CA-8W-M12BK/GY/HD

Operating Temperature Specification applicable to non-terminated bulk fiber cable