

Zx4430 UHD Set-Tops

DVB, HEVC, Ultra-HD Set-Tops with 802.11ac Wi-Fi

FEATURES

- Android TV[™] compliant platform
- Netflix Compliant (subject to Netflix/operator certification)
- RDK 2.x ready and supports traditional Pay-TV middleware
- 2x2 dual-band selectable IEEE 802.11ac Wi-Fi
- Industry-standard DRM support including pre-integration with Microsoft® PlayReady®, Widevine®, and ARRIS SECUREMEDIA® DRM
- Support for a range of Conditional Access System options available, including ARRIS TITANIUM
- The range includes models for OTT, DVB-C, DVB-S2, DVB-T2 or hybrid service providers
- Ultra-HD with support for a wide range of HDR formats including HDR10, HLG and Dolby Vision (optional dependant on royalty)
- HDMI™ 2.1
- Secure Bootloader

PRODUCT OVERVIEW

ARRIS presents a range of stylish, high-quality UHD (4K) set-tops in a small form factor, with models for cable, satellite, terrestrial, and OTT operators. The Zx4430 is an Android TV compliant DVB platform which uses the latest technologies to reduce power consumption and increase processing capabilities.

High Quality Video Experience - Ultra-HD, 10-bit colour and High Dynamic Range deliver four times the resolution of full HD, improved colour reproduction and a wider luminance range for an image that's even closer to reality, all at frame rates that allow fast-moving action with reduced blurring. The Zx4430 includes HDR<>SDR conversion for video and graphics, allowing the seamless use of legacy UIs on HDR displays, and the viewing of HDR content on conventional displays without the need for simulcasting.

Enables a wide choice of User Experience – a high-performance processor, 3D OpenGL and fast DDR4 memory give the platform the power to support a wide range of middlewares including Android TV to deliver a modern user experience.

Connectivity - the Zx4430 is a highly-connected unit with integrated IEEE 802.11ac dual band wireless and Fast Ethernet. USB 2.0 allows the connection of additional storage devices for functions such as time-shift TV. The Bluetooth Low Energy remote control option supports voice search and allows for hidden installation.

© 2017 ARRIS Enterprises, LLC. All rights reserved.

HEVC H.265

HDMI™ 2.1



	LANTC	
PRODUCT VAR ZC4430 DVB-C.		
	HEVC, Ultra-HD Cable Set-Top 02.11ac 2x2 Wi-Fi	
	DVB-S2 HEVC, Ultra-HD Satellite Set-Top with 802.11ac 2x2 Wi-Fi	
	DVB-T2, HEVC, Ultra-HD Terrestrial Set-Top with 802.11ac 2x2 Wi-Fi	
	DVB multi-standard (on request), HEVC, Ultra-HD, Dual-Core Set-Top with 802.11ac 2x2 Wi-Fi	
GENERAL SPEC	CIFICATIONS	
Core Processor		
Processing	Dual-core, 7000 DMIPS	
Graphics		
Technology	3D OpenGL ES3.0	
Memory		
RAM	2 GB DDR4	
Application Flash	8 GB eMMC	
Boot Flash	4 MB SPI NOR (optional)	
Video Decode / En	code	
Decoders/Resolution	ons Single up to 4kp60 10bit	
HDR formats suppo	orted HDR10, HLG and Dolby Vision	
Encoders	None	
Profiles	HEVC H.265 up to Main10@L5.1; AVC H.264 up to MP@L4.2; MPEG-2 up to MP@HL VP9 Profile 0 and 2	
Optional Codecs	VC1, WMV, DivX, VP8	
Audio Decode		
Sample Rate	32-192 kHz	
MPEG Audio	MPEG-1 Layers 1, 2, and 3 (MP3)	
MPEG-4 Audio	HE AAC v2 profile	
Dolby	Dolby Digital™, Dolby Digital Plus™ and Dolby ATMOS™ (option)	
Optional Codecs	WMA	

GENERAL SPECIFICATIONS - CONTINUED			
DVB-C Cable Option(Z	C4430)		
Input	IEC 61169-24 Female		
Tuning Range	112-1002 MHz		
Input Signal Level	15 to +15 dBmV		
Tuner/Demodulator	Full Band Capture 2,4, 8 x DVB-C/ITU J83-A,B,C		
Symbol Rate	4.0-6.952 Msym/s with notional support up to 7 Msym/s		
Modulation	16-, 32-, 64-, 128- and 256-QAM		
DVB-S2 Satellite Option	n (ZS4430)		
Input	2 x IEC 61169-24 Female		
Tuning Range	250-2350 MHz		
Input Signal Level	-65 to -25 dBm		
Tuner/Demodulator	2x Wideband tuners and up to 8x QPSK/8PSK demodulators compliant t EN 300 421 and EN 302 307 DVB-S/S2		
Symbol Rate	2-45 Msym/s		
LNB Supply	350 mA continuous supply		
LNB Control	13/18 V, 22-kHz tone		
DiSEqC	2.0 and SatCR		
DVB-T2 Terrestrial Opt	ion (ZT4430)		
Input	IEC 61169-2 Female		
Tuning Range	174-216 MHz (VHF) 470-806 MHz (UHF)		
Input Signal Level	-94 to -23 dBm		
Tuner/Demodulator	DVB-T/T2 tuner and demodulator		
Standards	EN 300 744 and EN302 755 Digital TV Group D-Book Nordig Unified Specification		



GENERAL SPECIFICATIONS - CONTINUED			
Wi-Fi			
Radio	2x2 802.11ac dual-band selectable		
Bandwidth	20, 40 and 80Mhz Support		
Beamforming	TX and RX		
Modulation	BPSK,QPSK,16QAM,64QAM,256QAM		
PHY rate	867 Mbps 5Ghz 300 Mbps 2.4GHz		
Front Panel			
Remote Control	IR, Bluetooth		
Indicators	2 LEDs, Blue/ Red standby indicator		
Buttons	One power button		
Rear Panel			
RF Input	As listed on previous page		
Digital AV	HDMI™ 2.1		
Analogue AV	None		
USB	USB 2.0 Type A 500 mA		
Ethernet	RJ-45 Fast Ethernet		
CAS	SIM-style smartcard (option)		
Power	DC input		

GENERAL 31 ECH 1C	AHONS - CONTINUED	
CAS and Security		
Secure Processor	Yes	
Interface	SIM-style compliant to ISO 7816	
HDCP	HDCP 2.2	
DRM Support	ARRIS SecureMedia® DRM Microsoft PlayReady® Widevine®	
CAS Support	ARRIS TITANIUM CAS ARRIS Secure Bootloader	
Physical		
Dimensions	120mm (W) x 120mm (D) x 40mm (H)	
Power		
EU Code-of-Conduct compliant		
Compliant to Energy Using Products Legislation EC No 1275/2008 and amendment EU 801/2013		
External PSU, localised according to region		

GENERAL SPECIFICATIONS - CONTINUED

CUSTOMER CARE

Contact Customer Care for product information and sales:

- United States: 866-36-ARRIS
- International: +1-678-473-5656





HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. Dolby, Dolby Audio, and the double-D symbol are trademarks or registered trademarks of Dolby Laboratories.

Zx4430-UHD-Set-Tops

(x1 08-2017