

DC60XU | DC60Xu Zapper Cable Set-Top

Base Product



ATSC, MPEG-4, HD Cable Digital Terminal Adapter

- All Digital for use in Digital Migrations
- Advanced User Interface
- In-Band Only
- Simple channel up/down plus numbers on remote control
- HDMI Cable
- RF Out Cable
- Remote Control
- External Plug Top Power Supply
- User Manual

The DC60Xu provides a cost-effective and secure way for cable operators to transition to digital by enabling the viewing of digital programming on HDMI equipped TV sets.

The ARRIS DC60Xu HD DTA is an ultra compact, low cost adaptor that converts broadcast MPEG 2 and 4 Standard Definition and High Definition QAM to a digital HDMI, and an analogue RF output. A virtual analog cable experience is provided with simple channel up/down and direct channel entry. All messaging to the DTA is carried In-Band, one way, with no return path. The DC60Xu supports standards based DVB-CSA, DES-ECB and SCTE 52 field-selectable modes for content decryption. A download of content protection software is required to activate content security.

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Product Type	Cable video device

General Specifications

Front Panel Interfaces	Bi-Color Power LED indicator IR receiver
Graphics	2D graphics engine Channel number and network text ID rendering on channel change Graphics presented on HDMI and RF simultaneously
Memory	128 MB SDRAM 8 MB Serial Flash
Tuner	Cable
Video Formats	HD

Dimensions

Height	26.416 mm 1.04 in
Width	109.982 mm 4.33 in
Length	81.026 mm 3.19 in