

760242874 | MFC-LCF-09-5Y-12-PACK



Qwik-Fuse Connector, LC, OM3/OM4/OM5, Aqua, for 250µm/900µm, 12 per pack

OBSOLETE

Replaced By:

760258743

Qwik-Fuse Connector, LC, OM3/OM4/OM5, Aqua, for 250µm/900µm, 12 per pack

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Fiber connector
Product Brand	LazrSPEED® Qwik
Product Series	Qwik-Fuse

General Specifications

Body Style	BTW
Color, boot	Aqua
Color, housing	Aqua
Ferrule Geometry	Factory polished
Interface	LC/UPC
Interface Feature	Field Installable Fusion splice

Dimensions

Tube Length	32 mm 1.26 in
Compatible Cable Diameter	0.25 mm 0.01 in 0.9 mm 0.035 in

Material Specifications

Ferrule Material	Zirconia
------------------	----------

Mechanical Specifications

Cable Retention Strength, maximum0.74 lb @ 0 ° | 1.03 lb @ 0 °

Optical Specifications

Fiber ModeMultimode

Fiber TypeOM3 | OM4 | OM5, LazrSPEED® wideband

Optical Components StandardANSI/TIA-568. 3-D | IEC 61753-1

Insertion Loss, maximum0.25 dB

Insertion Loss, typical0.1 dB

Return Loss, minimum30 dB

Environmental Specifications

Operating Temperature-40 °C to +75 °C (-40 °F to +167 °F)

Packaging and Weights

Packaging quantity12

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant/Exempted

