2291216-9 | KJ610-GN



KJ-Series Modular Jack, RJ45, Cat6 Unshielded, Green

OBSOLETE

This product was discontinued on: August 31, 2024

Replaced By:

2291216-GN KJ610-GN

KJ-Series Modular Jack, RJ45, Cat6 Unshielded, Green

Product Classification

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America

PortfolioNETCONNECT®Product TypeModular jackProduct SeriesKJ Series

General Specifications

ANSI/TIA Category 6

Cable TypeUnshieldedColorGreen

Conductor Type Solid | Stranded

Integrated Dust Cover Type None

Mounting Hubbell® faceplates | Leviton® faceplates | Panduit®

faceplates

Outlet Type Keystone

Termination Tool 110 Punchdown tool | SL Termination tool

Termination Type IDC

Transmission Standards ANSI/TIA-568-C.2 | ISO/IEC 11801 Class E

Wiring T568A | T568B

Dimensions

Panel Cutout, recommended 14.79 x 19.31 mm (0.58 x 0.76 in)

Page 1 of 3



2291216-9 | KJ610-GN

Panel Thickness, recommended 1.6 mm | 0.063 in

Height 16.13 mm | 0.635 in

Width 16.48 mm | 0.649 in

Depth 30.48 mm | 1.2 in

Compatible Insulated Conductor Diameter, maximum 1.27 mm | 0.05 in

Contact Plating Thickness 1.27 µm

Compatible Conductor Gauge, solid 24–22 AWG

Compatible Conductor Gauge, stranded 26–24 AWG

Electrical Specifications

Remote Powering Fully supports the safe delivery of power over LAN cabling described

by IEEE 802.3bt (Type 4) and complies with the unmating under electrical load requirements prescribed by IEC 60512-99-002

PoE Durability

Supports IEEE 802.3bt Type 4 (90 W) applications greater than 3000

plug to jack mating cycles

Material Specifications

Contact Base Material Beryllium copper

Contact Plating Material Gold

Material Type Polycarbonate

Mechanical Specifications

Plug to Jack Mating Cycles Complies to IEC 60603-7 series

Environmental Specifications

Flammability Rating UL 94 V-0

Packaging and Weights

Packaging quantity 1

Packaging Type Bag

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant

Page 2 of 3

2291216-9 | KJ610-GN

UK-ROHS

Compliant

