

FHD-X01D



DLX® Fiber Optic Hardened Drop Cable Assembly, DLX-stub, universal flat locatable/toneable

OBSOLETE

This product was discontinued on: July 31, 2024

Replaced By:

HCA-X01D Fiber Optic Drop Cable Assembly, PRODIGY™ Connector w/DLX converter factory installed to Stub, USD Toneable Cable

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Product Type	Fiber drop cable assembly
Product Brand	DLX®
Product Series	FHD
Ordering Note	Drops are automatically coiled 0 to 1,000 ft (305 m), unless spool option "L" or "R" is specified for this range of length Drops are automatically spooled at 1,001 ft (306 m) with connector B deploying first from spool

General Specifications

Cable Type	Locatable - Universal Flat
Connector A, quantity	1
Color, boot A	Black
Color, connector A	Black
Interface, Connector A	Hardened mini-size DLX
Interface, Connector B	Unterminated
Jacket Color	Black
Total Fibers, quantity	1
Transmission Standards	IEC 61753-1 IEC 61754-4 IEC 61755


Dimensions

Cable Assembly Length Range (m)	1 – 750
---------------------------------	---------

FHD-X01D

Cable Assembly Length Range (ft)	50 – 2000
Cable Outer Diameter	4.4 x 7.4 mm (0.17 x 0.29 in)

Ordering Tree



* Cable Type K not available with LC & SC Options

** Cable Length shown as an example, additional cable lengths available upon request up to 2,000 ft. (600 m).


*** Special Request Feature not available with cable types K.

**** Drops are automatically coiled 0 to 1,000 ft. unless "L" or "R" is specified for this range of length.

***** Drops are automatically spooled at 1,001 ft. with Connector B deploying first from spool. Add "L" to lengths over 1,001 ft. if Connector A needs to deploy first.

***** Includes pulling sock - 25 lbs. of pulling force

Representative Image



Mechanical Specifications

Minimum Bend Radius, loaded	100 mm 3.937 in
Minimum Bend Radius, unloaded	150 mm 5.906 in
Tensile Load, long term, maximum	450 N 101.164 lbf
Tensile Load, short term, maximum	1300 N 292.252 lbf
Cable Crush Resistance, maximum	44 N/mm 251.246 lb/in

FHD-X01D

Optical Specifications

Fiber Mode	Singlemode
Fiber Type	G.657.A2/B2
Insertion Loss, maximum, connector A	0.4 dB
Insertion Loss, typical	0.16 dB
Return Loss, minimum, connector A	65 dB

Environmental Specifications

Installation temperature	-30 °C to +70 °C (-22 °F to +158 °F)
Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Storage Temperature	-40 °C to +75 °C (-40 °F to +167 °F)
Environmental Space	Outdoor, buried
Jacket UV Resistance	UV stabilized
Qualification Standards	NEMA type 6, 10 ft waterhead Telcordia GR-20 Telcordia GR-3120

Packaging and Weights

Cable weight	36 kg/km 24.191 lb/kft
Packaging quantity	1

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant/Exempted
UK-ROHS	Compliant/Exempted

