

PS-1900-73



PowerShift® Module, 2 separate 2430 watts circuits per module

- Reduced capital/operating expenditures
- Engineering flexibility
- Future-ready design

Product Classification

Product Type	Module
Product Brand	PowerShift Macro®
Product Series	V2 V3

Dimensions

Height	41.402 mm 1.63 in
Width	101.6 mm 4 in
Depth	351.79 mm 13.85 in

Electrical Specifications

Input Current Range	0-57 A @ -38Vdc
Input Voltage Range	-38 to -58 Vdc
Input Voltage, nominal	-54 Vdc
Output Current Range	0-33 A
Output Voltage Range	-48 to -73 Vdc
Output Voltage Ripple	400 mVpp
Output Voltage, nominal	-56 Vdc
Electrical Safety Standard	CE IEC 60950 UL cUL
Electromagnetic Compatibility/Interference (EMC/EMI)	EN 55022 Class A
Power Efficiency	93 %
Power Efficiency, nominal	97 %
Programmable RRU Voltage, nominal	-56 Vdc
Total Output Power	2430 W, input voltage dependent

Environmental Specifications

PS-1900-73

Relative Humidity	95%, non-condensing
Ambient Temperature	-40 °C -40 °F 65 °C 149 °F
Mean Time Between Failures (MTBF) at Temperature	300,000 h @ 25 °C
Packaging and Weights	
Packaging quantity	1