760252501 | MDU-TAP-18-50/50



Multi Dwelling unit Terminal access point with SC-APC shuttered connectors, unbalanced optical divider 50%/50% and splitter 1:8

- Extremely small form reduces space requirments needed within the building
- Different tap ratio's allows networks to be optimized to reduce loss and improve reach
- Pre-installed splitters protected and sealed
- Suitable for in-building environment
- Utilizes shuttered SC/APC adapters providing a safe working environment
- In-molded color coded label for identification of tap ratio with possiblility of an QR code
- Optional cable attachment for strength relief and aditional cover for the adapters/connectors
- Plug and play solution allows for reduced installation skill requirments and greatly improves speed of installation

Product Classification

Portfolio C	CommScope®
-------------	------------

Product Type	MDU tap

General Specifications

Functionality	Patching Splitting	
Adapter Type	Input (1) Output (8) Thru (1)	
Adapters, quantity	10	
Color	Light gray	
Distribution Type	8-port tap	
Interface	SC/APC	
Mounting	Wall	
Split Ratio	50/50	
Dimonsions		

Dimensions

Height	100 mm 3.937 in
Width	75 mm 2.953 in
Depth	60 mm 2.362 in

Ordering Tree

Page 1 of 3

©2025 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: February 10, 2025



760252501 | MDU-TAP-18-50/50

MDU - TAP - SCU18 - X X / X X - X				
	ТАР Туре		Magnet Option	
	1:8 symmetrical optical splitter only	М	With magnet	
NN/NN	(Terminating TAP)	'blank'	Without magnet	
50/50	50/50% unbalanced			
60/40	0/40 60/40% unbalanced			
70/30 70/30% unbalanced				
80/20	80/20 80/20% unbalanced			
85/15	85/15 85/15% unbalanced			
90/10	90/10% unbalanced			

Material Specifications

Material Type

Acrylonitrile butadiene styrene (ABS)

Optical Performance

Identification color	Tap/Thru split ratio %	Drop port attenuation (insertion loss) median (dB)	Drop port attenuation (insertion loss) max (dB)	Thru port attenuation (insertion loss) max (dB)
Violet	Terminating	9,50	10,50	NA
Orange	50/50	13,90	14,90	4,10
Red	60/40	14,32	15,32	2,73
Blue	70/30	15,51	16,51	2,22
White	80/20	17,25	18,25	1,25
Yellow	85/15	19,79	20,79	1,13
Green	90/10	20,54	21,54	0,73

Optical Specifications

Fiber Mode

Singlemode

Environmental Specifications

Environmental Space Indoor | Riser

Flammability RatingUL 94 V-0

Packaging and Weights

Height, packed 120 mm | 4.724 in

Page 2 of 3

©2025 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: February 10, 2025

COMMSCOPE®

760252501 | MDU-TAP-18-50/50

Width, packed	170 mm 6.693 in
Depth, packed	295 mm 11.614 in
Packaging quantity	8
Packaging Type	Box Carton

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant



Page 3 of 3

©2025 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: February 10, 2025

