
## MC-DPM2M-6-B



Monopole Co-location Dual Pipe Mount Base Kit, 12 in to 50 in OD, 4 ft 9 in face, pipe ordered separately

#### **Product Classification**

**Product Type**Co-location dual pipe mount kit

General Specifications

**Mounting** Monopole, 304.8–1270 mm (12–50 in) OD

Pipe, quantity 0
Sectors, quantity 3

Dimensions

**Height** 254 mm | 10 in

**Face Width** 1.463 m | 4.8 ft

**Width** 1,447.8 mm | 57 in

Length 355.6 mm | 14 in Mounting Diameter, maximum 1270 mm | 50 in

Mounting Diameter, minimum 304.8 mm | 12 in

Pipe Outer Diameter 60.96 mm | 2.4 in

Stand-off Distance 355.6 mm | 14 in

**Mounting Circumference, maximum** 3,990.34 mm | 157.1 in

**Mounting Circumference, minimum** 1,196.34 mm | 47.1 in

Material Specifications

Material Type Hot dip galvanized steel

Mechanical Specifications

Wind Rating 120 mph (BWS) at 150 ft AGL | 140 mph (3-second gust) at 150 ft AGL using Exposure D

per FBC

**Wind Rating Criteria** Two 72 in x 8 in panel antennas per sector

Wind Rating Test Method TIA/EIA-222-G

ANDREW® an Amphenol company

# MC-DPM2M-6-B

### Packaging and Weights

Included Dual pipe frames | Pipe mounts | Ring mount

Packaging quantity 1

**Weight, net** 247.208 kg | 545 lb

### Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

\* Footnotes

Wind Rating BWS—Base Wind Speed; FBC—Florida Building Code

