## MC-DPM35M-6-72



GroundSmart® Monopole Co-location Dual Pipe Mount Kit, 12 in to 50 in OD, 4 ft 9 in face, includes pipes

Product Classification	
Product Type	Co-location dual pipe mount kit
General Specifications	
Mounting	Monopole, 304.8–1270 mm (12–50 in) OD
Pipe, quantity	6
Sectors, quantity	3
Dimensions	
Height	1,828.8 mm   72 in
Face Width	1.463 m   4.8 ft
Width	1,447.8 mm   57 in
Length	355.6 mm   14 in
Pipe Length	1,828.8 mm   72 in
Mounting Diameter, maximum	1270 mm   50 in
Mounting Diameter, minimum	304.8 mm   12 in
Pipe Outer Diameter	88.9 mm   3.5 in
Stand-off Distance	355.6 mm   14 in
Mounting Circumference, maximum	3,990.34 mm   157.1 in
Mounting Circumference, minimum	1,196.34 mm   47.1 in
Material Specifications	
Material Type	Hot dip galvanized steel

# Mechanical Specifications Wind Rating 120 mph (BWS) at 150 ft AGL | 140 mph (3-second gust) at 150 ft AGL using Exposure D per FBC Wind Rating Criteria Two 72 in x 8 in panel antennas per sector

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 12, 2025

## MC-DPM35M-6-72

Wind Rating Test Method

TIA/EIA-222-G

### Packaging and Weights

Included	Dual pipe frames   Pipe mounts   Ring mount
Packaging quantity	1
Weight, net	376.482 kg   830 lb

#### Regulatory Compliance/Certifications

#### Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

#### \* Footnotes

Agency

Wind Rating BWS-Base Wind Speed; FBC-Florida Building Code

Page 2 of 2