

HTB2



HTB2 Fiber Home Termination Box

The HTB2 is a compact fiber wall outlet for use at the final fiber termination point in the customer premises. The HFTP provides mechanical protection and managed fiber control in an attractive format suitable for use inside customer premises. A variety of possible fiber termination techniques are accommodated.

Features and benefits:

- Splicing to factory terminated pigtails
- Positive fiber management
- Direct termination with field installable connectors
- Attractive design for indoor use
- Can hold up to 2 fusion splice protectors (SMOUV and ANT)
- Compatible with 1 SC Simplex or 1 LC Duplex adaptor
- Up to 7 cable entry points
- Can be horizontally or vertically wall mounted

Product Classification

Regional Availability	India Latin America
Product Type	Fiber wall outlet
Product Series	HTB2

General Specifications

Adapters, quantity	1
Color	White
Front Cover Type	Screw-on
Lock Type	Standard screw
Mounting	Wall mount

Dimensions

Height	86 mm 3.386 in
Width	86 mm 3.386 in
Depth	22 mm 0.866 in

Material Specifications

HTB2

Material Type Acrylnitril Butadien Styrol (ABS)

Environmental Specifications

Operating Temperature -5 °C to +55 °C (+23 °F to +131 °F)

Environmental Space Indoor

Flammability Rating UL 94 V-0

Qualification Standards IEC 60529, IP40

Packaging and Weights

Packaging Type Box