## 2161003-5 | OCJ-LG-05MASIA-LG



Fiber Optic Patch Cord, Simplex, Singlemode, LC/APC to LC/APC, yellow, 5 m

#### **Product Classification**

Regional Availability EMEA

**Product Type** Fiber patch cord, simplex

Product Series OCJ

#### General Specifications

Connector A, quantity

Color, boot AGreenColor, connector AGreenConnector B, quantity1

Color, boot B Green
Color, connector B Green
Interface, Connector A LC/APC
Interface, Connector B LC/APC
Jacket Color Yellow
Total Fibers, quantity 1

#### **Dimensions**

Cable Assembly Length Range (m) 1 - 999

Cable Assembly Length Range (ft) 1 - 999


 Cord Length
 5 m | 16.404 ft

 Diameter Over Jacket
 1.8 mm | 0.071 in

### Ordering Tree



# 2161003-5 | OCJ-LG-05MASIA-LG



### Optical Specifications

**Fiber Mode** Singlemode

**Fiber Type** G.657.A1, TeraSPEED®

Performance Grade Superior B grade

Insertion Loss, maximum, connector A0.25 dBInsertion Loss, maximum, connector B0.25 dBReturn Loss, minimum, connector A60 dBReturn Loss, minimum, connector B60 dB

#### **Environmental Specifications**

**Operating Temperature**  $-40 \,^{\circ}\text{C} \text{ to } +70 \,^{\circ}\text{C} \, (-40 \,^{\circ}\text{F to } +158 \,^{\circ}\text{F})$ 

**Environmental Space** Low Smoke Zero Halogen (LSZH)

Packaging and Weights

Packaging quantity

COMMSCOPE®

# 2161003-5 | OCJ-LG-05MASIA-LG

### Regulatory Compliance/Certifications

#### Agency Classification

CHINA-ROHS Above maximum concentration value

ROHS Compliant/Exempted UK-ROHS Compliant/Exempted



#### \* Footnotes

**Performance Grade** Guarantee to meet IEC 61755-1 Random Mating requirement

