SFG22-12-3-126



G22 High Capacity Sector Frame, 12.5 ft face, includes three 126 in pipes; For patents, see www.cs-pat.com.

OBSOLETE

This product was discontinued on: March 22, 2023

Replaced By:

SFG22HD-12-4-126

G22HD High Capacity Sector Frame with 2 7/8in OD x 12.5ft face. Includes four 2 3/8in OD x 126in

antenna pipes.

Product Classification

Product Type High capacity Tower sector frame

General Specifications

Application 4G LTE antenna/radio mount

Mounting Angle 60°, 203.2 mm (8 in) | Straight or tapered legs up to 203.2 mm (8 in) OD

Patent Number Patent pending

Pipe, quantity 3

Tower Taper Non-tapered | Tapered

Dimensions

 Height
 3,200.4 mm | 126 in

 Face Width
 3.81 m | 12.5 ft

 Width
 3,810 mm | 150 in

 Pipe Length
 3,200.4 mm | 126 in

 Face Support Pipe Diameter
 60.325 mm | 2.375 in

Mounting Diameter, maximum 218.44 mm | 8.6 in

Mounting Diameter, minimum 38.1 mm | 1.5 in

Pipe Outer Diameter60.325 mm | 2.375 in

Stand-off Distance 1,193.8 mm | 47 in

Material Specifications

Material Type Hot dip galvanized steel

COMMSCOPE®

SFG22-12-3-126

Mechanical Specifications

Load Capacity With additional stiff arm at 300 ft AGL: 600 lb per pipe w/out ice / 1775 lb per pipe

including ice

Wind Rating For Specifications, please contact steelproducts@commscope.com or call 800-255-

1479

Wind Rating Test Method TIA/EIA-222-G

Wind Rating with Additional Stiff Arm 300 ft AGL: 120 mph (BWS) without ice /60 mph with ice

Environmental Specifications

EPA with 1/2 in (12 mm) radial ice $1.329 \text{ m}^2 \mid 14.3 \text{ ft}^2$ **EPA** without ice $0.975 \text{ m}^2 \mid 10.5 \text{ ft}^2$

Packaging and Weights

Included Frame | Pipe mounts | Plain end pipes (3) | Stiff arm | Tower attachment

Packaging quantity 1

Weight, net 229.518 kg | 506 lb

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Above maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

ROHS Compliant/Exempted

UK-ROHS Compliant





* Footnotes

Wind Rating BWS—Base Wind Speed; FBC—Florida Building Code

Wind Rating with Additional Stiff Arm BWS—Base Wind Speed; FBC—Florida Building Code

EPA with 1/2 in (12 mm) radial ice EPA—Effective Projected Area

EPA without ice EPA—Effective Projected Area

