# SFG23-12-3-126



G23 High Capacity Sector Frame, 12.5 ft face, includes three 126 in pipes; For patents, see www.cs-pat.com

### **OBSOLETE**

This product was discontinued on: March 22, 2023

Replaced By:

SFG23HDX-12-3-120 G23HDX High Capacity Sector Frame,12.5 ft x 2.88 in OD face pipes, includes three 2.88 OD x 120 in

antenna pipes

### **Product Classification**

**Product Type** High capacity Tower sector frame

## General Specifications

**Application** 4G LTE antenna/radio mount

Mounting Angle 60°, 203.2 mm (8 in) | Straight or tapered legs up to 203.2 mm (8 in) OD

Patent Number Patent pending

Pipe, quantity 3

Tower Taper Non-tapered | Tapered

#### Dimensions

 Height
 3,200.4 mm | 126 in

 Face Width
 3.81 m | 12.5 ft

 Width
 3,810 mm | 150 in

 Pipe Length
 3,200.4 mm | 126 in

Face Support Pipe Diameter60.325 mm | 2.375 inMounting Diameter, maximum218.44 mm | 8.6 in

Mounting Diameter, minimum38.1 mm | 1.5 inPipe Outer Diameter60.325 mm | 2.375 in

**Stand-off Distance** 1,226.82 mm | 48.3 in

Material Specifications



## SFG23-12-3-126

Material Type Hot dip galvanized steel

Mechanical Specifications

Wind Rating For Specifications, please contact steelproducts@commscope.com or call 800-255-1479

Wind Rating Test Method TIA/EIA-222-G

Packaging and Weights

Included Frame | Pipe mounts | Plain end pipes (3) | Stiff arm | Tower attachment

Packaging quantity 1

**Weight, net** 371.946 kg | 820 lb

Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

**ISO** 9001:2015

\* Footnotes

Wind Rating BWS—Base Wind Speed; FBC—Florida Building Code

