760255080 | PPL-SP-12LC-OM4-RPT-AS

Propel Multimode Splice Cassette, 12LC with internal shutters, OM4 ribbon fiber pigtail, pairs straight ULL

- Can be installed and removed from front or rear of panel
- This component requires 3 of the 12 lanes on the Propel Panel blade

Product Classification

Regional Availability	Asia	Australia/New Zealand	EMEA	Latin America	North America
Portfolio	CommScope®
Product Type	Fiber cassette with ribbon pigtail
Product Brand	Propel
Product Series	PPL

General Specifications

Color, front	Aqua
Interface, front	LC/UPC
Interface, rear	Ribbon pigtail
Polarity	Pairs, straight
Shuttered	Yes
Total Fibers, quantity	12

Dimensions

Height	67.31 mm	2.65 in
Width	97.993 mm	3.858 in

Optical Specifications

Fiber Mode	Multimode
Fiber Type	G.657.A2
Insertion Loss, maximum	0.15 dB

Environmental Specifications

Qualification Standards	IEC 61753-1	TIA-568.3-D
Safety Standard	UL

COMMSCOPE®

Packaging and Weights

Included   Mass Fusion Splice Protection Sleeves

Packaging quantity   1

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

Included Products

FST-ACC006   –   Mass Fusion Splice Protector (See Specs for packaging size and MOQ)

COMMSCOPE®

FST-ACC006

Mass Fusion Splice Protector (See Specs for packaging size and MOQ)

Product Classification

Regional Availability	North America
Product Type	Fiber protection sleeve
Ordering Note	Minimum order quantity (MOQ) is 5 pieces

General Specifications

Splicing Type	Heat shrink, mass fusion

Environmental Specifications

Storage Temperature	-40 °C to +85 °C (-40 °F to +185 °F)

Packaging and Weights

Packaging quantity	5

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

COMMSCOPE®