


# F-CLAMP-B-1B



KwikClamp™ Hanger for power & fiber cables, 7-22 mm, single stack, round or flat mounting; includes hardware

## Product Classification

Product Type	Hanger kit
Product Brand	KwikClamp™
Ordering Note	ANDREW® standard product in Europe, the Middle East, and Africa   Minimum order quantity (MOQ) is 1 box

## General Specifications

Cables per Hanger	1
Color	Black
Hanger Type	KwikClamp™ hanger
Mounting	3–25 mm angle iron   3–25 mm flat plate   Round Member 8–25 mm

## Dimensions

Maximum Stack Height	1
Height	137 mm   5.394 in
Width	32 mm   1.26 in
Length	42 mm   1.654 in
Compatible Cable Diameter Range	7-22 mm
Compatible Diameter, maximum	22 mm   0.866 in
Compatible Diameter, minimum	7 mm   0.276 in
Hanger Spacing, maximum	1.83 m   6.004 ft

## Electrical Specifications

Return Loss Effect, maximum	0.1 dB
DTF Effect, maximum	0.1 dB

## Material Specifications

Material Type	EPDM rubber   Engineered plastic   Stainless steel
---------------	--

# F-CLAMP-B-1B

---

## Mechanical Specifications

**Vibration Survival** ≥4 hours at resonant frequency

## Environmental Specifications

**Operating Temperature** -40 °C to +70 °C (-40 °F to +158 °F)

**Corrosion Resistance, minimum with no degradation** ≥500 hours in salt spray chamber

**Environmental Strength Capability** Five times cable weight

**UV Resistance, minimum with no degradation** ≥124 hours exposure in accelerated UV life chamber, testing duration 1344 hrs

## Packaging and Weights

**Height, packed** 15.5 cm | 6.102 in

**Width, packed** 30.5 cm | 12.008 in

**Length, packed** 35.5 cm | 13.976 in

**Included** Hardware

**Packaging quantity** 63

**Weight, gross** 6.5 kg | 14.33 lb

## \* Footnotes

**Maximum Stack Height** Fiber, Hybrid, Power