


LSX-ODF

Base Product



LSX Fiber Optic Distribution Frame

CommScope's LSX solution is designed to fit a variety of termination, splice and storage applications. Each frame option is built to industry standards to ensure commonality with patch cord routing, slack storage and fiber protection. The frame is shipped complete with front cable management, top and bottom troughs.

The termination and splice LSX-288 solution utilizes a traditional frame designed to fit a variety of termination, splice and storage applications. This front load frame is built to ensure commonality with patch cord routing, slack storage and fiber protection. Available accessories include panels, lower trough, interbay management panels (IMPs) and end guards.

The traditional LSX universal frame provides the framework for managing a cross-connect or interconnect fiber system. Use this frame for applications requiring lower density panels (12-144 terminations).

Product Classification

Regional Availability	Latin America North America
Product Type	Frame
Product Series	LSX

General Specifications

Access	Front
Application	For use with LSX panels
Color	Putty white
Growth Configuration	Unloaded
Mounting	Concrete floor

Dimensions

Height	2,133.6 mm 84 in
Width	584 mm 22.992 in
Depth	305 mm 12.008 in

LSX-ODF

Material Specifications

Finish	Powder coated
Material Type	Steel

Environmental Specifications

Environmental Space	Indoor
----------------------------	--------

Packaging and Weights

Included	Cable management
Packaging quantity	1
Packaging Type	Crate Pallet