## 760151290 | 360-IPR-MFTPA-E-HD6B-1U-24



SYSTIMAX 360™ GigaSPEED X10D® Evolve High Density Shielded Angled Modular Panel, 24 port

## Product Classification

Regional Availability	Asia   Australia/New Zealand   EMEA   Latin America   North America
Portfolio	SYSTIMAX®
Product Type	RJ45 patch panel
Product Brand	GigaSPEED X10D®   SYSTIMAX 360™
Product Series	HGS Series
General Specifications	
ANSI/TIA Category	6A
Cable Type	Shielded
Color	Cool gray   Satin chrome
Conductor Type	Solid   Stranded
Intelligence Type	iPatch® ready
Panel Style	Angled
Rack Type	EIA 19 in
Rack Units	1
Termination Type	IDC
Total Ports, quantity	24
Transmission Standards	ANSI/TIA-568-D.2   ISO/IEC 11801 Class E
Wiring	T568A   T568B
Dimensions	
Height	44.45 mm   1.75 in
Width	482.6 mm   19 in
Depth, with cable management	266.7 mm   10.5 in
Compatible Conductor Gauge, solid	22 AWG   24 AWG

Page 1 of 3

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: February 1, 2024



## 760151290 | 360-IPR-MFTPA-E-HD6B-1U-24

Compatible Conductor Gauge, stranded	22 AWG   24 AWG
Electrical Specifications	
Dielectric Withstand Voltage, RMS, contact-to-contact	1,000 Vac @ 60 Hz
Insulation Resistance, minimum	500 MOhm
Material Specifications	
Contact Plating Material	Precious metals
Material Type	High-impact, flame retardant, thermoplastic   Powder- coated steel
Termination Contact Plating	Nickel
Mechanical Specifications	
Plug Insertion Life, minimum	750 times
Plug Insertion Life, test plug	IEC 60603-7 compliant plug
Plug Retention Force, minimum	133 N   29.9 lbf
Environmental Specifications	
Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Relative Humidity	Up to 95%, non-condensing
Flammability Rating	UL 94 V-0
Safety Standard	UL   cUL
Packaging and Weights	
Packaging quantity	1
Weight, net	0.839 kg   1.85 lb
Regulatory Compliance/Certifications	

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

Page 2 of 3

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: February 1, 2024

COMMSCOPE®





Page 3 of 3

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: February 1, 2024

