

#### Double Block Hanger for 1-5/8 in coaxial cable

## **Product Classification**

Product Type Hanger kit

Ordering Note CommScope® standard product (Global)

General Specifications

Cables per Hanger 2

**Color** Black

**Hanger Type** Double block hanger

Mounting 3/8 in (M10) drilled cable ladder

**Dimensions** 

Maximum Stack Height 3

**Height** 48 mm | 1.89 in

 Width
 71.1 mm | 2.799 in

 Length
 136.9 mm | 5.39 in

**Compatible Cable Diameter Range** 49–51.1 mm

Compatible Diameter, maximum51.1 mm2.012 inCompatible Diameter, minimum49 mm1.929 in

Nominal Size 1-5/8 in

**Electrical Specifications** 

Return Loss Effect, maximum0.1 dBDTF Effect, maximum0.1 dB

Material Specifications

Material Type Engineered plastic

Page 1 of 2

# BHD-158

# **Environmental Specifications**

Operating Temperature  $-40 \,^{\circ}\text{C}$  to  $+85 \,^{\circ}\text{C}$  ( $-40 \,^{\circ}\text{F}$  to  $+185 \,^{\circ}\text{F}$ )

**Environmental Strength Capability**Double cable weight

**UV Resistance, minimum with no degradation** ≥100 hours exposure in accelerated UV life chamber

Packaging and Weights

 Height, packed
 5.1 cm | 2.008 in

 Width, packed
 25.4 cm | 10 in

 Length, packed
 30.5 cm | 12.008 in

Packaging quantity 10

**Weight, gross** 1.38 kg | 3.042 lb

# Regulatory Compliance/Certifications

#### Agency Classification

CHINA-ROHS Below maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant



### \* Footnotes

Maximum Stack Height Fiber, Hybrid, Power

