

## Double Block Hanger for 7/8 in coaxial cable

### **Product Classification**

Product Type Hanger kit

Ordering Note CommScope® standard product (Global)

General Specifications

Cables per Hanger 2

**Color** Black

**Hanger Type** Double block hanger

Mounting 3/8 in (M10) drilled cable ladder

**Dimensions** 

Maximum Stack Height 3

 Height
 42.9 mm | 1.689 in

 Width
 40.1 mm | 1.579 in

 Length
 80 mm | 3.15 in

 Compatible Cable Diameter Range
 27.7–28.2 mm

Compatible Diameter, maximum28.2 mm | 1.11 inCompatible Diameter, minimum27.7 mm | 1.091 in

Nominal Size 7/8 in

**Electrical Specifications** 

 Return Loss Effect, maximum
 0.1 dB

 DTF Effect, maximum
 0.1 dB

Material Specifications

Material Type Engineered plastic

Page 1 of 2

# BHD-78

# **Environmental Specifications**

Operating Temperature  $-40 \,^{\circ}\text{C}$  to  $+85 \,^{\circ}\text{C}$  ( $-40 \,^{\circ}\text{F}$  to  $+185 \,^{\circ}\text{F}$ )

**Environmental Strength Capability**Double cable weight

**UV Resistance, minimum with no degradation** ≥100 hours exposure in accelerated UV life chamber

Packaging and Weights

 Height, packed
 5.1 cm | 2.008 in

 Width, packed
 17.8 cm | 7.008 in

 Length, packed
 22.9 cm | 9.016 in

Packaging quantity 10

**Weight, gross** 0.56 kg | 1.235 lb

# Regulatory Compliance/Certifications

#### Agency Classification

CHINA-ROHS Below maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant



#### \* Footnotes

Maximum Stack Height Fiber, Hybrid, Power

